Toshiba P300 1TB



Artikel Herstellernummer EAN Toshiba 102568 HDWD110UZSVA 4051528216707

P300 - High-Performance Hard Drive

PERFORMANCE THAT MEETS DEMANDS

Toshiba's P300 3.5" internal hard drive delivers a high performance for professionals. With its dual-stage actuator, you can count on smooth, responsive computing. What's more, your data and media is secured with a ramp loading design, as well as a shock sensor. The P300 is available in capacities up to 3 TB.

POWERFUL STORAGE

The P300 is ideal for graphic designers and creative professionals looking for a powerful performance. Available in storage capacities of up to 3 TB, with fast read and write speeds and a secure design.

PERFORMANCE ALONGSIDE RELIABILITY

The P300's dual-stage actuator, available in the 2 TB and 3 TB models, improves positional accuracy, negating the effects on head-track alignment that vibrations can cause. This design makes for more precise, faster read and write speeds, and instant access to your data.

ADVANCED READ AND WRITE TECHNOLOGY

With Perpendicular Magnetic Recording technology – which can deliver more than three times the storage density of traditional recording, and accounts for the P300's high capacity – and Tunnel Magneto-Resistive recording technology – for improved stability – the P300 is equipped for fast and secure reading and writing of data.

KEEP DATA SECURE

The P300's design includes an internal shock sensor, ensuring no data is lost. In addition, ramp loading technology means that when your hard drive or desktop PC are being transported, the drive slider does not make contact with the disk and risk wearing or data loss.

INNOVATING WORLDWIDE

Toshiba is renowned the world over for 40 years of leading innovation – the power behind its range of hard drives is no exception. Designed for high capacity and excellent performance, you can be sure that Toshiba's wealth of experience in hard drives is at work in your desktop PC.

Zusammenfassung

P300 - High-Performance Hard Drive

PERFORMANCE THAT MEETS DEMANDS

Toshiba's P300 3.5" internal hard drive delivers a high performance for professionals. With its dual-stage actuator, you can count on

smooth, responsive computing. What's more, your data and media is secured with a ramp loading design, as well as a shock sensor. The P300 is available in capacities up to 3 TB.

POWERFUL STORAGE

The P300 is ideal for graphic designers and creative professionals looking for a powerful performance. Available in storage capacities of up to 3 TB, with fast read and write speeds and a secure design.

PERFORMANCE ALONGSIDE RELIABILITY

The P300's dual-stage actuator, available in the 2 TB and 3 TB models, improves positional accuracy, negating the effects on head-track alignment that vibrations can cause. This design makes for more precise, faster read and write speeds, and instant access to your data.

ADVANCED READ AND WRITE TECHNOLOGY

With Perpendicular Magnetic Recording technology – which can deliver more than three times the storage density of traditional recording, and accounts for the P300's high capacity – and Tunnel Magneto-Resistive recording technology – for improved stability – the P300 is equipped for fast and secure reading and writing of data.

KEEP DATA SECURE

The P300's design includes an internal shock sensor, ensuring no data is lost. In addition, ramp loading technology means that when your hard drive or desktop PC are being transported, the drive slider does not make contact with the disk and risk wearing or data loss.

INNOVATING WORLDWIDE

Toshiba is renowned the world over for 40 years of leading innovation – the power behind its range of hard drives is no exception. Designed for high capacity and excellent performance, you can be sure that Toshiba's wealth of experience in hard drives is at work in your desktop PC.

Toshiba P300 1TB, 3.5", 1 TB, 7200 RPM

Toshiba P300 1TB. HDD size: 3.5", HDD capacity: 1 TB, HDD speed: 7200 RPM

Merkmale

		Weight & dimensions	
Logistics data		Width	101.8 mm
		Height	26.1 mm
Harmonized System (HS)	84717050	Depth	147 mm
code		Weight	450 g
Technical details		Operational conditions	
Sustainability certificates	RoHS	Operating temperature (T-T)	0 - 60 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating vibration	0.67 G
Packaging data		Non-operating vibration	1.04 G
i donaging data		Operating shock	70 G
Quick start guide	Yes	Non-operating shock	350 G
Quantity 1		· · · ·	
		Features	
Power		1 04(4100	
		HDD size	3.5"
Power consumption (read)	6.4 W	HDD capacity	1 TB
Power consumption (write)	6.4 W	HDD speed	7200 RPM
Operating voltage	5 / 12 V	Interface	Serial ATA III
		Туре	HDD
		Component for	PC
		Storage drive buffer size	64 MB

HDD interface transfer rate

Average latency

6 Gbit/s 4.17 ms

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.