

Fujitsu Smart-UPS uninterruptible power supply (UPS)

Artikel	106550
Herstellernummer	FJX3000RMHV2UNC
EAN	0731304294009
Fujitsu	



Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.

Zusammenfassung

Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.

Fujitsu Smart-UPS, Line-Interactive, 3 kVA, 2700 W, Sine, 50/60 Hz, 208 V

Fujitsu Smart-UPS. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 6.3 min, Typical backup time at half load: 18 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS

Merkmale

Certificates

Compliance certificates	RoHS
-------------------------	------

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
Number of output IEC jumpers	2
SmartSlot	Yes

Packaging content

Rack mount kit	Yes
Cables included	RS-232
Manual	Yes

Packaging data

Package width	596 mm
Package depth	869 mm
Package height	85 mm
Package weight	45.4 kg

Weight & dimensions

Width	432 mm
Depth	667 mm
Height	85 mm
Weight	37.3 kg

Design

Form factor	Rackmount/Tower
Rack capacity	2U
Cable length	2.44 m
Product colour	Black
LED indicators	Battery replacement

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	6.3 min
Typical backup time at half load	18 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	Yes
Automatic battery test	Yes

Features

UPS topology	Line-Interactive
Output power capacity	3 kVA
Output power	2700 W
Waveform	Sine
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	645 J
Efficiency	98.5%
Emergency Power Off (EPO)	Yes
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Auto-restart	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.