

APC SMC1500I-2UC uninterruptible power supply (UPS)

Artikel	109358
Herstellernummer	SMC1500I-2UC
EAN	0731304332954
APC	



Peace of mind that comes with full equipment compatibility and reliability of a leader

Provides pure sine wave output which is recommended by server manufacturers using active power factor corrected (PFC) power supplies. Safety agency tested and approved means that you can deploy Smart-UPS with confidence that they meet or exceed the industry's most rigorous standards.

Smarter productivity with ability to tailor to your specific application needs

Intuitive LCD interface provides clear information with the ability to configure the UPS locally with easy to use navigation keys. Over 15 different programmable settings including switched outlet group control allow for application specific settings, thresholds and notifications.

Avoids costly power problems by keeping your IT equipment and data safe and available

Network grade power conditioning protects from damaging surges and disruptive noise. Solid state automatic voltage regulation boosts low input voltage up to 30% and trims high voltage up to 12% without battery operation. Reliable battery back-up capacity to power through outages or gracefully shutdown systems

Low operating and maintenance costs with high efficiency, proven reliability and intelligent battery management

Patented green operating mode achieves efficiencies over 97%. Smart-ups was the first network UPS to be Energy Star certified. Intelligent battery management, pioneered by APC, maximizes battery performance and life through intelligent, precision temperature compensated charging. Dynamic battery replacement date indicator and automatic self tests insure battery reliability and warn in advance of needing replacement. Convenient, easy to connect, hot-swappable battery modules provide battery replacement without powering down. Designed and manufactured by APC for over 23 years, Smart-UPS is the world's most trusted network UPS with over 25 million units sold.

Save time with easy and convenient remote accessibility

Network manageable via serial, USB or optional ethernet. Includes Powerchute® Business Edition Software for convenient monitoring and control, safe operating system shutdown and innovative energy management capabilities.

Zusammenfassung

Peace of mind that comes with full equipment compatibility and reliability of a leader

Provides pure sine wave output which is recommended by server manufacturers using active power factor corrected (PFC) power

supplies. Safety agency tested and approved means that you can deploy Smart-UPS with confidence that they meet or exceed the industry's most rigorous standards.

Smarter productivity with ability to tailor to your specific application needs

Intuitive LCD interface provides clear information with the ability to configure the UPS locally with easy to use navigation keys. Over 15 different programmable settings including switched outlet group control allow for application specific settings, thresholds and notifications.

Avoids costly power problems by keeping your IT equipment and data safe and available

Network grade power conditioning protects from damaging surges and disruptive noise. Solid state automatic voltage regulation boosts low input voltage up to 30% and trims high voltage up to 12% without battery operation. Reliable battery back-up capacity to power through outages or gracefully shutdown systems

Low operating and maintenance costs with high efficiency, proven reliability and intelligent battery management

Patented green operating mode achieves efficiencies over 97%. Smart-ups was the first network UPS to be Energy Star certified. Intelligent battery management, pioneered by APC, maximizes battery performance and life through intelligent, precision temperature compensated charging. Dynamic battery replacement date indicator and automatic self tests insure battery reliability and warn in advance of needing replacement. Convenient, easy to connect, hot-swappable battery modules provide battery replacement without powering down. Designed and manufactured by APC for over 23 years, Smart-UPS is the world's most trusted network UPS with over 25 million units sold.

Save time with easy and convenient remote accessibility

Network manageable via serial, USB or optional ethernet. Includes Powerchute® Business Edition Software for convenient monitoring and control, safe operating system shutdown and innovative energy management capabilities.

APC SMC1500I-2UC, Line-Interactive, 1.5 kVA, 900 W, Sine, 170 V, 300 V

APC SMC1500I-2UC. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

Merkmale

Technical details

Sustainability certificates Green Premium

Logistics data

Products per pallet 16 pc(s)
Harmonized System (HS) code 85078000

Packaging data

Rack mount kit Y
Cables included USB cable
Quick installation guide Y
Resource CD Y
Software CD Y

Battery

Operational conditions

Operating temperature (T-T) 0 - 40 °C
Storage temperature (T-T) -15 - 45 °C
Operating relative humidity (H-H) 0 - 95%
Storage relative humidity (H-H) 0 - 95%
Operating altitude 0 - 3000 m
Non-operating altitude 0 - 15000 m

Ports & interfaces

AC outlet types C13 coupler
Power plug C14 coupler
AC outlets quantity 4 AC outlet(s)
USB port Y
USB 2.0 ports quantity 1
Serial interface Y
Serial interface type RJ-45

Weight & dimensions

Width 432 mm
Depth 477 mm

Battery technology	Sealed Lead Acid (VRLA)
Battery life (max)	6 year(s)
Battery recharge time	3 h
Hot-swap battery	Y
Automatic battery test	Y
Cold start	Y

Height	86 mm
Weight	28.6 kg
Package width	594 mm
Package depth	603 mm
Package height	251 mm
Package weight	31.9 kg

Design

Form factor	Rackmount
Rack capacity	2U
Product colour	Black
Display type	LCD
LED indicators	Y
Certification	C-tick, CE, CSA, GOST, UL 1778, VDE

Features

UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	900 W
Waveform	Sine
Input operation voltage (min)	170 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Y
Surge energy rating	459 J
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	46 dB
Audible alarm(s)	Y
Web-based management	Y
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	Y
Temperature voltage compensation	Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.