

Canon CanoScan 2995C010 scanner



Artikel	111437
Herstellernummer	2995C010
EAN	4549292119770
Canon	

Benefit from easy functionality with a straightforward USB connection in CanoScan LiDE 300's compact and affordable package. Complex menus are a thing of the past; 4 EZ operations give you the functions you need at the touch of a button, including scan to email or PDF, copy and Auto Scan, which chooses the perfect settings for you every time. You can reap the rewards of impressive speed (A4 300 dpi scan in 10 seconds) and quality too – receive scans of up to 2,400x4,800 dpi and eliminate distortion with Auto Document Fix and Auto Photo Fix¹ for clear, accurate and pristine results.

Zusammenfassung

Benefit from easy functionality with a straightforward USB connection in CanoScan LiDE 300's compact and affordable package. Complex menus are a thing of the past; 4 EZ operations give you the functions you need at the touch of a button, including scan to email or PDF, copy and Auto Scan, which chooses the perfect settings for you every time. You can reap the rewards of impressive speed (A4 300 dpi scan in 10 seconds) and quality too – receive scans of up to 2,400x4,800 dpi and eliminate distortion with Auto Document Fix and Auto Photo Fix¹ for clear, accurate and pristine results.

Canon CanoScan LiDE 300 flatbed scanner, Black, 216 x 297 mm, 2400 x 2400 DPI, 48 bit, 48 bit, 16 bit, 8 bit

Canon CanoScan LiDE 300 flatbed scanner, Black. Maximum scan size: 216 x 297 mm, Optical scanning resolution: 2400 x 2400 DPI, Input colour depth: 48 bit. Scanner type: Flatbed scanner, Product colour: Black. Sensor type: CIS, Light source: RGB LED. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4. Standard interfaces: USB 2.0

Merkmale

Logistics data

Harmonized System (HS) code	84716070
-----------------------------	----------

Paper handling

Maximum ISO A-series paper size	A4
ISO A-series sizes (A0...A9)	A4
Letter	Yes

Packaging content

Bundled software	Scan Gear for Win Scan Utility for Win
------------------	----------------------------------------

Ports & interfaces

USB port	Yes
USB version	2.0

Standard interfaces	USB 2.0
---------------------	---------

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Operating relative humidity (H-10 - 90% H)	

Performance

Sensor type	CIS
Light source	RGB LED

System requirements

Windows operating systems supported	Yes
Mac operating systems supported	Yes

Design

Scanner type	Flatbed scanner
Product colour	Black
Built-in display	No

Power

Power supply type	USB
Power consumption (typical)	4.5 W
Power consumption (standby)	0.3 W

Weight & dimensions

Width	250 mm
Depth	367 mm
Height	42 mm
Weight	1.7 kg

Scanning

Maximum scan size	216 x 297 mm
Optical scanning resolution	2400 x 2400 DPI
Colour scanning	Yes
Input colour depth	48 bit
Output colour depth	48 bit
Input greyscale depth	16 bit
Output greyscale depth	8 bit

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.