Xilence M403PRO



Artikel Herstellernummer EAN Xilence 111697 XC029 4044953502262

The compact M403PRO with its tower design is the new multi-socket cooler from the Performance C Series. Three high-performance copper heat pipes dissipate 150W waste heat to the innumerable cooling fins. These reasons make the cooler ideal for powerful multi-core processors. Additionally, the heat transmission between CPU and cooler is very evenly and efficient due to the direct contact of heat pipes and CPU. The mounting material make this cooler suitable for all current AMD and INTEL sockets. The scope of delivery not only includes the heat sink tower, as well as the 120mm PWM fan but also a holding module for Intel sockets 1150/1151/1155/1156/2011/2066/1200 and AMD sockets FM2+/FM1/FM2/AM2/AM2+/AM3 and a tube of thermal paste. For the correct installation an illustrated manual is included.

Zusammenfassung

The compact M403PRO with its tower design is the new multi-socket cooler from the Performance C Series. Three high-performance copper heat pipes dissipate 150W waste heat to the innumerable cooling fins. These reasons make the cooler ideal for powerful multi-core processors. Additionally, the heat transmission between CPU and cooler is very evenly and efficient due to the direct contact of heat pipes and CPU. The mounting material make this cooler suitable for all current AMD and INTEL sockets. The scope of delivery not only includes the heat sink tower, as well as the 120mm PWM fan but also a holding module for Intel sockets 1150/1151/1155/1156/2011/2066/1200 and AMD sockets FM2+/FM1/FM2/AM2/AM2+/AM3 and a tube of thermal paste. For the correct installation an illustrated manual is included.

Xilence M403PRO, Cooler, 12 cm, 500 RPM, 1800 RPM, 14.2 dB, 25.6 dB

Xilence M403PRO. Type: Cooler, Fan diameter: 12 cm, Rotational speed (min): 500 RPM, Rotational speed (max): 1800 RPM, Noise level (low speed): 14.2 dB, Noise level (high speed): 25.6 dB, Bearing type: Hydraulic. Width: 71.6 mm, Depth: 120 mm, Height: 14 mm. Product colour: Black

Merkmale

Logistics data

Harmonized System (HS) 8473308 code

Performance

Suitable location	Processor
Type	Cooler
Fan diameter	12 cm
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155
	(Socket H2), LGA 1156 (Socket

Power

Rated voltage 12 V Thermal Design Power (TDP) 150 W

Design

Product colour	Black
Base plate material	Aluminium
Number of fins	40
Fins material	Aluminium
Number of heat pipes	3
Fan connector	4-pin

H), LGA 1200 (Socket H5), LGA 2011 (Socket R), Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2, Socket FM2+ 500 RPM 1800 RPM 14.2 dB 25.6 dB

Weight & dimensions

Rotational speed (min)

Rotational speed (max)

Noise level (low speed)

Noise level (high speed)

Bearing type

Width	71.6 mm
Depth	120 mm
Height	14 mm
Weight	420 g
Fan dimensions (W x D x H)	120 x 120 x 25 mm
Heat pipes diameter	6 mm
Cable length	0.36 m
Package width	108 mm
Package depth	124 mm
Package height	156 mm

Hydraulic

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.