

Epson TM-T20III



Artikel
Herstellernummer
EAN
Epson

115092
C31CH51011
8715946669649

Epson TM-T20III (011): USB + Serial, PS, Blk, EU

The combination of its fast print speeds, high reliability and economical operation, make this printer a must-have for small retail and speciality stores, hospitality venues and grocery stores.

Affordable

This easy-to-use model is our entry-level POS receipt printer and has an 80mm printing width. Its Automatic Paper Reduction feature reduces top and bottom margins, line feed width and barcode height, allowing for flexible receipt printing. This monitors and controls the amount of paper used. Paper costs are minimised by printing the top logo of the next receipt before cutting, so the top margin is further reduced by 12mm.

Reliable

With the mean time between failures (MTBF) of 360,000 hours and a mechanism life of 15 million lines, you can rely on the TM-T20III in high-volume printing environments.

Flexible

The TM-T20III comes with a built-in USB interface. You can select from two models: 1) USB + Serial, 2) Ethernet, making the model a long-term investment as it is possible to switch connectivity at any time.

Fast

Its print speed of 250mm/sec can save you time and its competitive price and running costs can save you money; ideal for when you need to beat queues quickly.

Zusammenfassung

Epson TM-T20III (011): USB + Serial, PS, Blk, EU

The combination of its fast print speeds, high reliability and economical operation, make this printer a must-have for small retail and speciality stores, hospitality venues and grocery stores.

Affordable

This easy-to-use model is our entry-level POS receipt printer and has an 80mm printing width. Its Automatic Paper Reduction feature reduces top and bottom margins, line feed width and barcode height, allowing for flexible receipt printing. This monitors and controls the amount of paper used. Paper costs are minimised by printing the top logo of the next receipt before cutting, so the top margin is further reduced by 12mm.

Reliable

With the mean time between failures (MTBF) of 360,000 hours and a mechanism life of 15 million lines, you can rely on the TM-T20III in high-volume printing environments.

Flexible

The TM-T20III comes with a built-in USB interface. You can select from two models: 1) USB + Serial, 2) Ethernet, making the model a long-term investment as it is possible to switch connectivity at any time.

Fast

Its print speed of 250mm/sec can save you time and its competitive price and running costs can save you money; ideal for when you need to beat queues quickly.

Epson TM-T20III, Direct thermal, POS printer, 203 x 203 DPI, 250 mm/sec, 22.6 cpi, Text, Graphic, Barcode

Epson TM-T20III. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired, USB connector: USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: Black

Merkmale

Design

Product colour Black

Print technology

Column capacity 48/64

Technical details

Lifetime 15000000 lines

Network

Ethernet LAN No

Wi-Fi No

Paper handling

Maximum roll diameter 8.3 cm

Supported paper width 80 mm

Packaging content

Drivers included Yes

Quick start guide Yes

AC adapter included Yes

Operational conditions

Operating temperature (T-T) 5 - 45 °C

Storage temperature (T-T) -10 - 50 °C

Operating relative humidity (H-10 - 90%
H)

Storage relative humidity (H- 10 - 90%
H)

Power

Power source type AC
AC input voltage 24 V
Power consumption 1800 mA
Power consumption (standby) 100 mA

Weight & dimensions

Width 140 mm
Depth 199 mm
Height 146 mm
Weight 1.7 kg

Packaging data

Cables included AC
Quantity per pack 1 pc(s)
Package width 192 mm
Package depth 235 mm
Package height 280 mm
Package weight 2.62 kg

Printing

Maximum resolution 203 x 203 DPI
Print speed 250 mm/sec
Character density 22.6 cpi
Printing characters Text, Graphic, Barcode
Character sets ANK
Print technology Direct thermal
Type POS printer

Ports & interfaces

USB port Yes
USB 2.0 ports quantity 1
USB connector USB Type-B
Serial interface Yes
Serial interface type RS-232

Other features

Buffer size	4 KB
Mean cycles between failures (MCBF)	60000000
Print head life	150.000.000 Impulse
Print head life	150 million characters

Connectivity technology	Wired
Serial ports quantity	1
Standard interfaces	RS-232, USB 2.0

Logistics data

Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per master (outer) case	4 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	295 mm
Master (outer) case gross weight	0 g
Products per pallet	112 pc(s)
Products per pallet layer	16 pc(s)
Pallet gross weight	0 g
Products per pallet (UK)	168 pc(s)
Products per pallet layer (UK)	24 pc(s)

Features

Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	360000 h
Cutter	Yes
Half-cutter	Yes
Autocutter durability	1.5 million cuts
Paper save function	Yes
Print head life	150 km
Country of origin	Philippines
Mounting position	Horizontal/Vertical
Wall mountable	Yes
Built-in sensors details	Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor
Safety	UL, CSA, TÜV
Certification	FCC-Class A, CE, EN55022-Class A

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.