

Ubiquiti UniFi 16-Port PoE

Artikel	115491
Herstellernummer	USW-16-POE
EAN	0817882028547
Ubiquiti	



Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Zusammenfassung

Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Ubiquiti UniFi 16-Port PoE, Managed, L2/L3, Gigabit Ethernet (10/100/1000), Power over Ethernet (PoE), Rack mounting, 1U

Ubiquiti UniFi 16-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. Switching capacity: 36 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 44 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U

Merkmale

Logistics data

Harmonized System (HS) code 85176990

Security

Authentication type IEEE 802.1x, RADIUS

Management features

Switch type Managed
Switch layer L2/L3

Operational conditions

Operating temperature (T-T) -5 - 40 °C
Operating relative humidity (H-10 - 90% H)

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity 16
Basic switching RJ-45 Ethernet ports type Gigabit Ethernet (10/100/1000)
SFP module slots quantity 2

Power

Power supply included Y
AC input voltage 100 - 240 V
AC input frequency 50 - 60 Hz
DC input voltage 44 - 57 V

Power over Ethernet (PoE)

Power over Ethernet (PoE) Y
Power over Ethernet plus (PoE+) ports quantity 8
Power over Ethernet (PoE) power per port 32 W
Total Power over Ethernet (PoE) budget 48 W

Weight & dimensions

Width 442.4 mm
Depth 200 mm
Height 43.7 mm
Weight 2.8 kg

Data transmission

Switching capacity 36 Gbit/s
Throughput 18000 Mpps
Forwarding rate 26.78 Mpps
Static route Y
Jumbo frames support Y

Design

Rack mounting Y
Form factor 1U
Product colour Silver
LED indicators Activity, Link, PoE, Speed, System
Certification CE, FCC, IC

Network

Networking standards IEEE 802.3af, IEEE 802.3at
Port mirroring Y
Full duplex Y
Flow control support Y
Auto MDI/MDI-X Y
Spanning tree protocol Y
Auto-sensing Y
VLAN support Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.