

TP-Link OC200 gateway/controller

Artikel	115597
Herstellernummer	OC200 V1.1
EAN	6935364084233
TP-Link	



Dedicated In Network Centralized Management

The OC200 Omada Cloud Controller delicate to provide centralized management for the whole Omada network. Monitor statistics in real-time, view a graphical analysis of network traffic, create a captive portal, upgrade and reboot your system, and easily scale your network to boost your business.

Free Cloud Management – Anywhere, Anytime

Omada offers free cloud access to its centralized management platform. Take your network with you, wherever you go.

Industry Leading Hardware Design

Equipped with an advanced hardware design and the latest chipset, OC200 has the impressive processing power to support the massive management of your business network.

Guest Network with Facebook Wi-Fi and SMS Login

Visitors have access to secure Wi-Fi with captive portal and wireless isolation technology. Newly added SMS authentication simplifies the connection process, while Facebook authentication raises the social media profile of your business.

Even More Convenient with Omada App

Remotely access and configure the OC200 from the convenience of your smartphone, wherever you are in the world.

Zusammenfassung

Dedicated In Network Centralized Management

The OC200 Omada Cloud Controller delicate to provide centralized management for the whole Omada network. Monitor statistics in real-time, view a graphical analysis of network traffic, create a captive portal, upgrade and reboot your system, and easily scale your network to boost your business.

Free Cloud Management – Anywhere, Anytime

Omada offers free cloud access to its centralized management platform. Take your network with you, wherever you go.

Industry Leading Hardware Design

Equipped with an advanced hardware design and the latest chipset, OC200 has the impressive processing power to support the massive management of your business network.

Guest Network with Facebook Wi-Fi and SMS Login

Visitors have access to secure Wi-Fi with captive portal and wireless isolation technology. Newly added SMS authentication simplifies the connection process, while Facebook authentication raises the social media profile of your business.

Even More Convenient with Omada App

Remotely access and configure the OC200 from the convenience of your smartphone, wherever you are in the world.

TP-Link Omada Cloud Controller, Black, CE, FCC, RoHS, 1000 MHz, 1024 MB, DDR3, 4000 MB

TP-Link Omada Cloud Controller. Product colour: Black, Certification: CE, FCC, RoHS. Processor frequency: 1000 MHz, Internal memory: 1024 MB, Internal memory type: DDR3. Ethernet LAN data rates: 10,100 Mbit/s, Networking standards: IEEE 802.3af, IEEE 802.3at. Security algorithms: SSID, WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Management platform: L3

Merkmale

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Software

Compatible operating systems	Windows 10, 8, 7, Vista, XP; MAC OS; NetWare, UNIX; Linux
------------------------------	---

Network

Ethernet LAN data rates	10,100 Mbit/s
Networking standards	IEEE 802.3af, IEEE 802.3at

Packaging content

Cables included	LAN (RJ-45)
Quick installation guide	Y

Ports & interfaces

USB 2.0 ports quantity	1
Ethernet LAN (RJ-45) ports	2

Design

Product colour	Black
LED indicators	Y
Certification	CE, FCC, RoHS

Packaging data

Package width	135 mm
Package depth	128 mm
Package height	70 mm

Security

MAC address filtering	Y
Security algorithms	SSID, WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
VLAN support	Y

Weight & dimensions

Width	99.8 mm
Depth	98 mm
Height	25 mm

Management features

Management platform	L3
Web-based management	Y
Reset button	Y
Syslog	Y

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Power

Power consumption (typical)	5 W
Input voltage	5 V
Input current	1 A
Power over Ethernet (PoE)	Y
DC input voltage	5 V

Performance

Control display unit	N
Built-in processor	Y
Processor frequency	1000 MHz
Number of processors installed	1
Internal memory	1024 MB
Internal memory type	DDR3
Flash memory	4000 MB

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.