

Fujitsu S26361-F4542-L75 uninterruptible power supply (UPS)



Artikel	117557
Herstellernummer	S26361-F4542-L75
EAN	4051554426736
Fujitsu	

Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.

Zusammenfassung

Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.

Fujitsu S26361-F4542-L75, Line-Interactive, 0.75 kVA, 500 W, 230 V, C13 coupler, 6 AC outlet(s)

Fujitsu S26361-F4542-L75. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, AC outlets quantity: 6 AC outlet(s). Typical backup time at full load: 5 min, Typical backup time at half load: 16 min. Form factor: Tower, Product colour: Black. Width: 138 mm, Depth: 363 mm, Height: 161 mm

Merkmale

Logistics data		Features	
Harmonized System (HS) code	85078000	UPS topology	Line-Interactive
		Output power capacity	0.75 kVA
		Output power	500 W
		Output operation voltage (min)	230 V

Battery

Typical backup time at full load	5 min
Typical backup time at half load	16 min

Design

Form factor	Tower
Product colour	Black

Ports & interfaces

AC outlet types	C13 coupler
AC outlets quantity	6 AC outlet(s)
USB 2.0 ports quantity	1
Serial ports quantity	1

Weight & dimensions

Width	138 mm
Depth	363 mm
Height	161 mm
Weight	13.2 kg

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.