

Ubiquiti UniFi USW?FLEX



Artikel
Herstellernummer
EAN
Ubiquiti

120740
USW-FLEX
0817882027595

PoE Flexibility

The USW-Flex supports a maximum PoE output budget of 46W when powered by 60W 802.3bt PoE++. Four ports offer auto-sensing 802.3af PoE output to power multiple devices on the network.

Versatile Mounting

The USW-Flex can be installed horizontally or vertically making it ideal for desktop, magnetic wall-mount, and pole-mount installations.

Indoor/Outdoor Design

The USW-Flex is designed for indoor or outdoor use. With its weatherproof housing and versatile mounting options, the USW-Flex provides both flexibility and durability for environments with extreme temperature variations

Compatible Products

The USW-Flex powers a variety of products, including the UniFi Video Camera G3 Flex, UniFi Video Camera G4 Pro, and UniFi AC Mesh AP, which use 802.3af PoE. To enable its maximum power budget of 46W, the USW-Flex can be powered by the USW-Industrial switch, which provides 60W of 802.3bt PoE++.

Seamless Integration

A single instance of the UniFi Controller running in the cloud can manage multiple UniFi sites within a centralized interface. Each site is logically separated and has its own network monitoring, configuration, maps, statistics, and admin accounts.

Zusammenfassung

PoE Flexibility

The USW-Flex supports a maximum PoE output budget of 46W when powered by 60W 802.3bt PoE++. Four ports offer auto-sensing 802.3af PoE output to power multiple devices on the network.

Versatile Mounting

The USW-Flex can be installed horizontally or vertically making it ideal for desktop, magnetic wall-mount, and pole-mount installations.

Indoor/Outdoor Design

The USW-Flex is designed for indoor or outdoor use. With its weatherproof housing and versatile mounting options, the USW-Flex provides both flexibility and durability for environments with extreme temperature variations

Compatible Products

The USW-Flex powers a variety of products, including the UniFi Video Camera G3 Flex, UniFi Video Camera G4 Pro, and UniFi AC Mesh AP, which use 802.3af PoE. To enable its maximum power budget of 46W, the USW-Flex can be powered by the USW-Industrial

switch, which provides 60W of 802.3bt PoE++.

Seamless Integration

A single instance of the UniFi Controller running in the cloud can manage multiple UniFi sites within a centralized interface. Each site is logically separated and has its own network monitoring, configuration, maps, statistics, and admin accounts.

Ubiquiti UniFi USW?FLEX, Managed, L2, Gigabit Ethernet (10/100/1000), Full duplex, Power over Ethernet (PoE), Wall mountable

Ubiquiti UniFi USW?FLEX. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex, Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. Power over Ethernet (PoE). Wall mountable

Merkmale

		Ports & interfaces	
Data transmission		Basic switching RJ-45 Ethernet ports quantity	5
Jumbo frames support	Yes	Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Logistics data		Power over Ethernet (PoE)	
Harmonized System (HS) code	85176990	Power over Ethernet (PoE)	Yes
Performance		Power over Ethernet (PoE) ports quantity	4
Firmware upgradeable	Yes	Weight & dimensions	
Management features		Width	122.5 mm
Switch type	Managed	Depth	107.1 mm
Switch layer	L2	Height	28 mm
Operational conditions		Weight	230 g
Operating temperature (T-T)	-40 - 55 °C	Design	
Operating relative humidity (H-5 - 95% H)		Rack mounting	No
		Product colour	White
		LED indicators	Activity, Link, PoE, Status
		International Protection (IP) code	IP55
		Wall mountable	Yes
		Network	
		Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
		10G support	No
		Full duplex	Yes
		Auto MDI/MDI-X	Yes
		VLAN support	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.