

Ubiquiti UniFi Switch Lite 8 PoE

Artikel	121447
Herstellernummer	USW-LITE-8-POE
EAN	0810010071101
Ubiquiti	



The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices.

Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.

Zusammenfassung

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices.

Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.

Ubiquiti UniFi Switch Lite 8 PoE, Managed, L2, Gigabit Ethernet (10/100/1000), Power over Ethernet (PoE), Wall mountable

Ubiquiti UniFi Switch Lite 8 PoE. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Switching capacity: 8 Gbit/s. Networking standards: IEEE 802.3at. DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable

Merkmale

Data transmission

Switching capacity 8 Gbit/s

Logistics data

Harmonized System (HS) 85176990

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power connector	DC-in jack

Power

code

Management features

Switch type Managed
Switch layer L2

Network

Networking standards IEEE 802.3at
10G support No

Operational conditions

Operating temperature (T-T) -15 - 40 °C
Operating relative humidity (H-10 - 90%
H)

Power supply included Yes
Number of power supply units 1
DC input voltage 54 V
Power consumption (typical) 60 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) Yes
Power over Ethernet (PoE) type PoE+
supported
Power over Ethernet plus (PoE+) 4
ports quantity
Power over Ethernet (PoE) power30 W
per port

Weight & dimensions

Width 163.7 mm
Depth 99.6 mm
Height 31.7 mm
Weight 450 g

Design

Rack mounting No
Stackable No
Product colour White
LED indicators Yes
Wall mountable Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.