

Synology E10G21-F2 network card

Artikel	122866
Herstellernummer	E10G21-F2
EAN	4711174723829
Synology	



Cost-effective upgrade for Synology NAS and IP-SAN

The E10G21-F2 adapter gives you more connectivity options with support for SR and LR transceivers and DAC options. Dual 10GbE ports help alleviate network bandwidth limitations and support Link Aggregation (network bonding) for increased resiliency in the face of network disruptions. CPU offloading technologies reduce network transfer overhead on the host system's processor to boost system performance.

Zusammenfassung

Cost-effective upgrade for Synology NAS and IP-SAN

The E10G21-F2 adapter gives you more connectivity options with support for SR and LR transceivers and DAC options. Dual 10GbE ports help alleviate network bandwidth limitations and support Link Aggregation (network bonding) for increased resiliency in the face of network disruptions. CPU offloading technologies reduce network transfer overhead on the host system's processor to boost system performance.

Synology E10G21-F2, Internal, Wired, PCI Express, Fiber, 10000 Mbit/s, Black, Blue, Silver

Synology E10G21-F2. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Fiber. Maximum data transfer rate: 10000 Mbit/s. Product colour: Black, Blue, Silver

Merkmale

Logistics data

Harmonized System (HS) code 85176990

Operational conditions

Operating temperature (T-T) 0 - 40 °C

Design

Component for	Server
Product colour	Black, Blue, Silver
Internal	Y
Compatible products	FS series:FS2500, FS6400, FS3600, FS3400, FS3017, FS2017, FS1018 SA series:SA3600, SA3400, SA3200D UC series:UC3200 22 series:DS3622xs+, DS2422+ 21

Storage temperature (T-T) -20 - 60 °C

Operating relative humidity (H-5 - 95%

H)

Weight & dimensions

Width	168 mm
Depth	69 mm
Height	17.3 mm

series:RS4021xs+, RS3621xs+,
RS3621RPxs, RS2821RP+,
RS2421RP+, RS2421+,
RS1221RP+, RS1221+,
DS1821+, DS1621xs+, DS1621+
20 series:RS820RP+, RS820+ 19
series:RS1619xs+, DS2419+,
DS2419+II, DS1819+ 18
series:RS3618xs, RS2818RP+,
RS2418RP+, RS2418+,
DS3018xs, DS1618+ 17
series:RS18017xs+, RS4017xs+,
RS3617xs+, RS3617RPxs,
DS3617xs, DS3617xsII

Network

Maximum data transfer rate	10000 Mbit/s
Networking standards	IEEE 802.3ad, IEEE 802.3ae
Full duplex	Y
Jumbo frames support	Y
Jumbo frames	9000

Ports & interfaces

Connectivity technology	Wired
Host interface	PCI Express
Interface	Fiber
Fiber optic connector	SFP+
PCI version	3.0
PCI Card form factor	Full-height (low-profile)

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.