Seagate Enterprise ST6000NM019B internal hard drive



Artikel Herstellernummer EAN Seagate 125936 ST6000NM019B 8719706022095

Purpose-built for enterprise applications and workloads

Trusted. Efficient. Versatile

For everything Enterprise storage, there's Exos E — the safest and most powerful way to traverse the datasphere and harness its full potential. Always on and always working, the Exos E series of hard drives is loaded with advanced options for optimal performance, reliability, security and user-definable storage management. Built on generations of industry-defining innovation, Exos E is designed to work and perform consistently in enterprise-class workloads.

Exos 7E10

Specifically designed to address the needs of storing unstructured data cost-effectively.

Zusammenfassung

Purpose-built for enterprise applications and workloads

Trusted. Efficient. Versatile

For everything Enterprise storage, there's Exos E — the safest and most powerful way to traverse the datasphere and harness its full potential. Always on and always working, the Exos E series of hard drives is loaded with advanced options for optimal performance, reliability, security and user-definable storage management. Built on generations of industry-defining innovation, Exos E is designed to work and perform consistently in enterprise-class workloads.

Exos 7E10

Specifically designed to address the needs of storing unstructured data cost-effectively.

Seagate Enterprise ST6000NM019B, 3.5", 6 TB, 7200 RPM

Seagate Enterprise ST6000NM019B. HDD size: 3.5", HDD capacity: 6 TB, HDD speed: 7200 RPM

Merkmale

Logistics data

Harmonized System (HS) 84717050 code

Power

Power consumption (typical)	11.03 W
Power consumption (idle)	7.06 W
Operating voltage	5 / 12 V

Operational conditions

Operating temperature (T-T)	5 - 60 °C
Non-operating vibration	5 G
Operating shock	70 G
Non-operating shock	300 G

Weight & dimensions

Width	101.8 mm	
Height	26.1 mm	
Depth	147 mm	
Weight	716 g	

Features

HDD size	3.5"	
HDD capacity	6 TB	
HDD speed	7200 RPM	
Interface	Serial ATA III	
Туре	HDD	
Component for	Disk array	
Storage drive buffer size	256 MB	
HDD interface transfer rate	6 Gbit/s	
Average latency	4.16 ms	
Uncorrectable Bit Error Rate (UBER)	< 1 per 10^15 bits read	
Rotational Vibration (RV) sensors Yes		
24/7 operation	Yes	
Mean time between failures (MTBF)	2000000 h	

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.