

Ubiquiti Networks Gateway Pro gateway/controller

Artikel	125945
Herstellernummer	UXG-PRO-EU
EAN	0810010073525
Ubiquiti Networks	



The UniFi Next-generation Gateway Pro (UXG Pro) is a powerful security gateway that delivers a versatile networking interface and enterprise-class threat management functionality to medium to large-sized networks. The UXG Pro is equipped with (2) WAN ports (GbE RJ45 and 10G SFP+) that provide failover support, as well as (2) LAN ports (GbE RJ45 and 10G SFP+) to provide the high-speed connectivity needed to support the most bandwidth-intensive applications. It also excels as a complete network security solution, offering a full suite of threat mitigation features, including deep packet inspection (DPI), intrusion detection and prevention systems (IDS/IPS), and layered firewall configuration. The UXG Pro can be paired with a Cloud Key Gen2 Plus to create a highly powerful and secure deployment that can be fully managed with the UniFi Network application (web/mobile).

Zusammenfassung

The UniFi Next-generation Gateway Pro (UXG Pro) is a powerful security gateway that delivers a versatile networking interface and enterprise-class threat management functionality to medium to large-sized networks. The UXG Pro is equipped with (2) WAN ports (GbE RJ45 and 10G SFP+) that provide failover support, as well as (2) LAN ports (GbE RJ45 and 10G SFP+) to provide the high-speed connectivity needed to support the most bandwidth-intensive applications. It also excels as a complete network security solution, offering a full suite of threat mitigation features, including deep packet inspection (DPI), intrusion detection and prevention systems (IDS/IPS), and layered firewall configuration. The UXG Pro can be paired with a Cloud Key Gen2 Plus to create a highly powerful and secure deployment that can be fully managed with the UniFi Network application (web/mobile).

Ubiquiti Networks Gateway Pro, 1U, Aluminum, Rack mounting, LAN, Power, 1700 MHz, 2048 MB

Ubiquiti Networks Gateway Pro. Rack capacity: 1U, Enclosure material: Aluminum, Mounting type: Rack mounting. Processor frequency: 1700 MHz, Internal memory: 2048 MB. Ethernet LAN data rates: 1000 Mbit/s. WAN connection: Ethernet (RJ-45). Input voltage: 200 - 240 V, Input frequency: 50 - 60 Hz, Power supply: 50 W

Merkmale

Logistics data		Ports & interfaces	
Harmonized System (HS) code	85176990	Ethernet LAN (RJ-45) ports	2
		WAN connection	Ethernet (RJ-45)
		Power	

Management features

Reset button	Y
--------------	---

Input voltage	200 - 240 V
Input frequency	50 - 60 Hz
Power supply	50 W

Network

Ethernet LAN data rates	1000 Mbit/s
-------------------------	-------------

Design

Rack capacity	1U
Enclosure material	Aluminum
Mounting type	Rack mounting
LED indicators	LAN, Power

Sustainability

Sustainability certificates	CE
-----------------------------	----

Weight & dimensions

Width	442.4 mm
Depth	285.6 mm
Height	43.7 mm
Weight	3.42 kg

Display

Touchscreen	Y
Display diagonal	3.3 cm (1.3")

Performance

Control display unit	Y
Built-in processor	Y
Processor frequency	1700 MHz
Number of processors installed	1
Internal memory	2048 MB

Operational conditions

Operating temperature (T-T)	-10 - 40 °C
Operating relative humidity (H-5 H)	95%

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.