

# Zebra DS2208

---



**Artikel**  
**Herstellernummer**  
**EAN**  
Zebra

126779  
DS2208-SR7U2100SGW  
8596375044401

## **AFFORDABILITY AND SIMPLICITY DELIVERED**

2D barcodes have made their way to your Point of Sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards.

Your 1D scanner can't capture the new 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store.

But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. And you can choose the model that best fits your POS needs — the corded DS2208 or the cordless DS2278. The DS2200 Series — the affordability your budget demands, with the deployment, ease of use and management simplicity your business requires.

## **Zusammenfassung**

---

### **AFFORDABILITY AND SIMPLICITY DELIVERED**

2D barcodes have made their way to your Point of Sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards.

Your 1D scanner can't capture the new 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store.

But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. And you can choose the model that best fits your POS needs — the corded DS2208 or the cordless DS2278. The DS2200 Series — the affordability your budget demands, with the deployment, ease of use and management simplicity your business requires.

Zebra DS2208, Handheld bar code reader, 1D/2D, LED, Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar Expanded, Interleaved 2 of 5,..., Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, PDF417, QR Code, TLC-39, 640 x 480 pixels

Zebra DS2208. Type: Handheld bar code reader, Scanner type: 1D/2D, Sensor type: LED. Connectivity technology: Wired, Standard interfaces: USB, RS-232, RS-485, Keyboard wedge. Product colour: Black, International Protection (IP) code: IP42, Certification: EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2.... Power source type: DC, Battery technology: Lithium-Ion (Li-Ion), Battery capacity: 2400 mAh. Weight: 161.6 g, Width: 66 mm, Depth: 99 mm

# Merkmale

## Logistics data

Harmonized System (HS) code	84716070
-----------------------------	----------

## Technical details

Sustainability certificates	RoHS
-----------------------------	------

## Packaging data

Cables included	Micro-USB
Charging base	No

## Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-5 - 95% H)	

## Performance

International Protection (IP) code	IP42
LED indicators	Yes
Product colour	Black
Certification	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B

## Ports & interfaces

Connectivity technology	Wired
Standard interfaces	USB, RS-232, RS-485, Keyboard wedge
Bluetooth version	4.0
Bluetooth Low Energy (BLE)	Yes

## Weight & dimensions

Width	66 mm
Depth	99 mm
Height	165 mm
Weight	161.6 g

## Power

Power source type	DC
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	2400 mAh
Battery life	100 h
AC adapter output voltage	5 V
Power consumption	250 mA

## Scanning

Type	Handheld bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar Expanded, Interleaved 2 of 5, MSI, U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, PDF417, QR Code, TLC-39
Optical sensor resolution (W x H)	640 x 480 pixels
Working distance	36.8 cm
Wavelength	645 nm
Tilt reading angle	-65 - 65°
Pitch reading angle	-65 - 65°
Yaw reading angle	-65 - 65°
Motion tolerance (cm/s)	13

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.