Epson EB-982W data projector



Artikel
Herstellernummer
EAN
Epson

126835 V11H987040 8715946680774

EB-982W

Optimise your presentation's potential with this bright WXGA projector that's capable of producing a large and scalable screen size. Excessive downtime is a thing of the past with this reliable projector that can deliver years of use before a replacement lamp is required or the air filter needs attention. It has a range of connectivity solutions and is fuss free to set up.

Excellent visibility for every presenter

With this WXGA projector, content will be bright, vivid and clear, ensuring that everyone can engage with the audience. Providing excellent visibility, this projector is scalable up to 280 inches and is bright even in high ambient lighting conditions. It's all thanks to the high 4,200-lumen output and 16,000:1 contrast ratio.

Minimal maintenance

Our reliable projectors and long-lasting lamps help to eliminate downtime and unnecessary service costs. Imagine what you could achieve with minimal interruptions - our projectors provide years of use before a replacement lamp is required.

Easy set up

Every working environment is different so you need a display solution that is simple to set up and position. With our wide 1.6x optical zoom and vertical/horizontal keystone correction, it's easy to get up and running quickly.

Utilise multiple devices

Capture your audiences' attention and nurture a collaborative environment with hassle-free connectivity solutions. With the iProjection App1, it's easy to display content from PCs and smart devices. The split-screen function can be utilised to show content from multiple devices simultaneously, while the moderator function lets you review content before it is displayed.

Zusammenfassung

EB-982W

Optimise your presentation's potential with this bright WXGA projector that's capable of producing a large and scalable screen size. Excessive downtime is a thing of the past with this reliable projector that can deliver years of use before a replacement lamp is required or the air filter needs attention. It has a range of connectivity solutions and is fuss free to set up.

Excellent visibility for every presenter

With this WXGA projector, content will be bright, vivid and clear, ensuring that everyone can engage with the audience. Providing excellent visibility, this projector is scalable up to 280 inches and is bright even in high ambient lighting conditions. It's all thanks to the high 4,200-lumen output and 16,000:1 contrast ratio.

Minimal maintenance

Our reliable projectors and long-lasting lamps help to eliminate downtime and unnecessary service costs. Imagine what you could

achieve with minimal interruptions - our projectors provide years of use before a replacement lamp is required.

Easy set up

Every working environment is different so you need a display solution that is simple to set up and position. With our wide 1.6x optical zoom and vertical/horizontal keystone correction, it's easy to get up and running quickly.

Utilise multiple devices

Capture your audiences' attention and nurture a collaborative environment with hassle-free connectivity solutions. With the iProjection App1, it's easy to display content from PCs and smart devices. The split-screen function can be utilised to show content from multiple devices simultaneously, while the moderator function lets you review content before it is displayed.

Epson EB-982W, 4200 ANSI lumens, 3LCD, WXGA (1280x800), 16000:1, 16:10, 584.2 - 7112 mm (23 - 280")

Epson EB-982W. Projector brightness: 4200 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 6500 h, Service life of light source (economic mode): 17000 h. Focal length range: 18.2 - 29.2 mm, Aperture range (F-F): 1.51 - 1.99, Zoom type: Manual. Video processing: 10 bit, Video colour modes: Blackboard, Cinema, Dynamic, Sports, sRGB. Serial interface type: RS-232C

Merkmale			
		Design	
Other features		Product type	Standard throw projector
		Product colour	White
Supported network protocols	PJLink	Placement	Ceiling, Desktop
		Cable lock slot	Υ
		Cable lock slot type	Kensington
oftware			
oftware support	via: AMX, Crestron (Network), Control4, Extron	Light source	
		Light source type	Lamp
		Service life of light source	6500 h
Technical details		Service life of light source	17000 h
		(economic mode)	
JSB display function	3 in 1: Image / Mouse / Sound	Lamp type	UHE
		Lamp power	230 W
Multimedia			
Built in speaker(s)	Υ	Lens system	
Built-in speaker(s) RMS rated power	16 W	Focal length range	18.2 - 29.2 mm
ino rated power	10 **	Aperture range (F-F)	1.51 - 1.99
		Zoom capability	Υ
		Zoom type	Manual
Network		Zoom ratio	1.6:1
Ethernet LAN	Υ	Throw ratio	1.38 - 2.24:1
Ethernet LAN (RJ-45) ports	1	THIOW TABLE	1.00 2.21.1
		Packaging content	
Features		Remote control included	V
	00.10		Y
Noise level (economic mode)	28 dB	Batteries included	Y AC LIDMI

Logistics data

Password protection

Noise level

Country of origin

Quantity per pack	1 pc(s)
Products per pallet	72 pc(s)

37 dB

Philippines

Power

Cables included

Quick start guide

Bundled software

WLAN adapter included

AC, HDMI

EasyMP Multi PC Projection, Epson Projektor Management

Υ

Products per pallet (UK) 72 pc(s)
Harmonized System (HS) 85286200

code

Operational conditions

Operating temperature (T-T) 5 - 35 °C
Storage temperature (T-T) -10 - 60 °C
Operating relative humidity (H-20 - 80%
H)
Storage relative humidity (H- 10 - 90%
H)

Video

Full HD	N
3D	N
Video processing	10 bit
Video colour modes	Blackboard, Cinema,
	Dynamic, Sports, sRGB

Power source	AC
Power consumption (typical)	327 W
Power consumption (standby)	0.3 W
Power consumption (economy mode)	225 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz

Ports & interfaces

USB 2.0 ports quantity	1
USB 2.0 Type-B ports quantity	1
Serial interface type	RS-232C
VGA (D-Sub) ports quantity	2
HDMI ports quantity	2
Composite video in	1
DVI port	N

Weight & dimensions

Width	309 mm	
Depth	282 mm	
Height	90 mm	
Weight	3.1 kg	
Package width	385 mm	
Package depth	395 mm	
Package height	175 mm	
Package weight	4.68 ka	

Projector

Screen size compatibility	584.2 - 7112 mm (23 - 280")
Projection distance (wide)	0.9 - 8.5 m
Projection distance (tele)	1.4 - 13.7 m
Projector brightness	4200 ANSI lumens
Projection technology	3LCD
Projector native resolution	WXGA (1280x800)
Contrast ratio (typical)	16000:1
Native aspect ratio	16:10
Number of colours	1.07 billion colours
Projector brightness (economic mode)	2600 ANSI lumens
Vertical scan range	100 - 120 Hz
Keystone correction, horizontal	-30 - 30°
Keystone correction, vertical	-30 - 30°
Matrix size	1.5 cm (0.59")

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.