

DELL UltraSharp U3223QE LED display



Artikel	127438
Herstellernummer	DELL-U3223QE
EAN	5397184567739
DELL	

Be your most productive on a 31.5-inch 4K monitor with brilliant color and contrast that features groundbreaking IPS Black technology and a connectivity hub.

Zusammenfassung

Be your most productive on a 31.5-inch 4K monitor with brilliant color and contrast that features groundbreaking IPS Black technology and a connectivity hub.

DELL UltraSharp 32 4K USB-C Hub Monitor - U3223QE, 80 cm (31.5"), 3840 x 2160 pixels, 4K Ultra HD, LCD, 8 ms, Silver

DELL UltraSharp 32 4K USB-C Hub Monitor - U3223QE. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Silver

Merkmale

Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------

Network

Wi-Fi	No
-------	----

Packaging data

Package weight	14.5 kg
----------------	---------

Design

Market positioning	Graphics design
Product colour	Silver
Front bezel colour	Black
Feet colour	Silver
Heavy metals free	Hg (mercury)
Compliance industry standards	ENERGY STAR certified Monitor. EPEAT registered where applicable. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage current requirements. Arsenic-Free glass and Mercury-Free for the panel only.

Multimedia

Built-in speaker(s)	No
Built-in camera	No

Sustainability

Sustainability certificates	RoHS, TCO, ENERGY STAR, EPEAT Gold
Doesn't contain	PVC/BFR, Arsenic

Packaging content

Stand included	Yes
Cables included	AC, DisplayPort, USB Type-C to USB Type-A, USB Type-C to USB Type-C
Quick start guide	Yes

Performance

NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes

Other features

DCI-P3 coverage	98%
Picture-by-Picture (PbP)	Yes
Maximum resolution	3840 x 2160 pixels
RJ-45 ports quantity	1
Power management	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m

Ergonomics

VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot	Yes
Height adjustment	Yes
Pivot	No
Swivelling	Yes
Swivel angle range	-30 - 30°
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
Plug and Play	Yes
Tilt adjustment	Yes

Weight & dimensions

Width (with stand)	712.6 mm
Depth (with stand)	233.2 mm
Height (with stand)	469.3 mm
Weight (with stand)	9.98 kg
Width (without stand)	712.6 mm
Depth (without stand)	55.8 mm
Height (without stand)	410 mm
Weight (without stand)	5.65 kg
Bezel width (side)	7.65 mm
Bezel width (top)	7.65 mm
Bezel width (bottom)	1.01 cm

Power

Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	E
Energy consumption (SDR) per 1000 hours	29 kWh
Energy consumption (HDR) per 1000 hours	26 kWh
Power consumption (typical)	29.4 W
Power consumption (standby)	0.3 W
Power consumption (max)	220 W
Power consumption (off)	0.2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	2.7 A
Power supply type	Internal
Energy efficiency scale	A to G

Ports & interfaces

Built-in USB hub	Yes
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB upstream port type	USB Type-C
Number of upstream ports	2

Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	5
USB Power Delivery	Yes
USB Power Delivery up to	90 W
HDMI	Yes
HDMI ports quantity	1
HDMI version	2.0
DisplayPorts quantity	2
Audio output	Yes
Headphone out	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	Yes

Display

Display diagonal	80 cm (31.5")
Display resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Native aspect ratio	16:9
Display technology	LCD
Panel type	IPS
Backlight type	LED
Touchscreen	No
Display brightness (typical)	400 cd/m ²
Response time	8 ms
Anti-glare screen	Yes
Screen shape	Flat
Supported video modes	1080i, 1080p, 480p, 720p, 576p
Contrast ratio (typical)	2000:1
Maximum refresh rate	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Response time (fast)	5 ms
Pixel pitch	0.18159 x 0.18159 mm
Pixel density	137.68 ppi
Horizontal scan range	15 - 140 kHz
Vertical scan range	23 - 86 Hz
Viewable size, horizontal	69.7 cm
Viewable size, vertical	39.2 cm
Display diagonal (metric)	80.01 cm
High Dynamic Range (HDR) supported	No
DDC/CI	Yes
Surface hardness	3H
RGB colour space	sRGB
sRGB coverage (typical)	100%
Heat dissipation	98.27 BTU/h

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.