

Teltonika PR1KCO28 network antenna



Artikel	127498
Herstellernummer	PR1KCO28
EAN	5903148916750
Teltonika	

Teltonika Combo LTE/ GPS/ Wi-Fi antenna
The MIMO Combo antenna consists of 5 integrated antennas: 2 LTE antennas, 2 Wi-Fi antennas and a GPS antenna. It is designed to be mounted on vehicle roofs.

Zusammenfassung

Teltonika Combo LTE/ GPS/ Wi-Fi antenna
The MIMO Combo antenna consists of 5 integrated antennas: 2 LTE antennas, 2 Wi-Fi antennas and a GPS antenna. It is designed to be mounted on vehicle roofs.

Teltonika PR1KCO28, 28 dBi, 1.57542-1.61; 0.698-0.96/1.71-2.69; 2.4-2.4835/4.9-5.825 GHz, 2 dBi, 2 dBi, 50 ?, MIMO directional antenna

Teltonika PR1KCO28. Antenna gain level (max): 28 dBi, Frequency band: 1.57542-1.61; 0.698-0.96/1.71-2.69; 2.4-2.4835/4.9-5.825 GHz, Antenna gain (2.4 GHz): 2 dBi. Antenna type: MIMO directional antenna, Antenna connector type: SMA, Connector gender: Female/Female. Power consumption: 15 mA, Input voltage: 3-5 V. Height: 55 mm, Diameter: 11 cm, Weight: 550 g

Merkmale

Logistics data

Harmonized System (HS) code	85177100
-----------------------------	----------

Technical details

Sustainability certificates	RoHS
-----------------------------	------

Power

--	--

Weight & dimensions

Height	55 mm
Diameter	11 cm
Weight	550 g

Performance

Frequency band	1.57542-1.61; 0.698-0.96/1.71-2.69; 2.4-2.4835/4.9-5.825 GHz
Antenna gain (2.4 GHz)	2 dBi
Antenna gain (5 GHz)	2 dBi
Impedance	50 ?

Power consumption	15 mA
Input voltage	3-5 V

Antenna gain level (max)	28 dBi
--------------------------	--------

Features

Antenna type	MIMO directional antenna
Antenna connector type	SMA
Connector gender	Female/Female
Polarization	Linear polarization
Voltage Standing Wave Ratio (VSWR)	2/2.5/3
International Protection (IP) code	IP67
Cable length	3 m
Cable type	5x RG174
Housing material	Acrylonitrile butadiene styrene (ABS)
Product colour	Black

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.