

Seasonic FOCUS SGX-750 (2021) power supply unit



Artikel	128211
Herstellernummer	FOCUS-SGX-750
EAN	4711173877110
Seasonic	

FOCUS SGX (2021)

The new line of Seasonic's FOCUS SGX is versatile in its application and powerful with a small footprint. It is a standard SFX unit, measuring at 125 mm (L) x 100 mm (W) x 63.5 mm (H). The FOCUS SGX (2021) is shipped with an SFX to ATX adapter bracket in the box, which allows the power supply to be mounted not only in the SFX form factor chassis, but also a standard ATX chassis should the user prefers to reserve more space for airflow inside the PC case. The Seasonic hybrid fan control is always enabled to optimize the cooling according to necessity.

Zusammenfassung

FOCUS SGX (2021)

The new line of Seasonic's FOCUS SGX is versatile in its application and powerful with a small footprint. It is a standard SFX unit, measuring at 125 mm (L) x 100 mm (W) x 63.5 mm (H). The FOCUS SGX (2021) is shipped with an SFX to ATX adapter bracket in the box, which allows the power supply to be mounted not only in the SFX form factor chassis, but also a standard ATX chassis should the user prefers to reserve more space for airflow inside the PC case. The Seasonic hybrid fan control is always enabled to optimize the cooling according to necessity.

Seasonic FOCUS SGX-750 (2021), 750 W, 100 - 240 V, 50 - 60 Hz, 10 A, 5 A, 100 W

Seasonic FOCUS SGX-750 (2021). Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 35 cm, SATA power cable length: 600 mm. Purpose: PC, Power supply unit (PSU) form factor: SFX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 9.2 cm. Width: 125 mm, Depth: 100 mm, Height: 63.5 mm

Merkmale

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Operational conditions

Design

Product colour	Black
Cooling type	Active
Fan diameter	9.2 cm
Number of fans	1 fan(s)

Performance

Operating temperature (T-T) 0 - 50 °C

Packaging data

Package type Box

Weight & dimensions

Width	125 mm
Depth	100 mm
Height	63.5 mm

80 PLUS certification	80 PLUS Gold
Purpose	PC
Power supply unit (PSU) form factor	SFX
Mean time between failures (MTBF)	100000 h

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Motherboard power cable length	35 cm
Number of SATA power connectors	6
SATA power cable length	600 mm
Peripheral (Molex) power connectors (4-pin)	3
Peripheral (Molex) power cable length	470,700 mm
CPU power connector (4+4 pin)	Y
CPU power cable length	40 cm
Cabling type	Modular

Power

Total power	750 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Maximum input current (@110V)	10 A
Maximum input current (@220V)	5 A
Combined power (+3.3V)	100 W
Combined power (+12V)	744 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V)	62 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.