

# Fanvil i62 video intercom system



Artikel	128497
Herstellernummer	I62
EAN	6937295602913
Fanvil	

Based on SIP and ONVIF protocols, i62 is a video door phone that integrates powerful functionalities of access control, intercom, and security protection. Featuring an aluminum alloy design and single speed-dial button, i62 delivers a high-quality elegant appearance. With high protection level IP66 and IK07, it is waterproof, dustproof and anti-collision in most outdoor environments. i62 allows users to make audio/video calls via a speed-dial button and a 2 Mega-pixel camera and achieve access control by different modes. With rich input and output interfaces, i62 is easy to link with other security devices and customize into various solutions in apartments, commercial buildings, communities and industrial parks.

## Zusammenfassung

Based on SIP and ONVIF protocols, i62 is a video door phone that integrates powerful functionalities of access control, intercom, and security protection. Featuring an aluminum alloy design and single speed-dial button, i62 delivers a high-quality elegant appearance. With high protection level IP66 and IK07, it is waterproof, dustproof and anti-collision in most outdoor environments. i62 allows users to make audio/video calls via a speed-dial button and a 2 Mega-pixel camera and achieve access control by different modes. With rich input and output interfaces, i62 is easy to link with other security devices and customize into various solutions in apartments, commercial buildings, communities and industrial parks.

Fanvil i62, Aluminium, IP67, IK07, Aluminium, Buttons, Outdoor

Fanvil i62. Product colour: Aluminium, International Protection (IP) code: IP67, IK code: IK07. Ethernet interface type: Fast Ethernet. Megapixel (approx.): 2 MP, Maximum image resolution: 1920 x 1080 pixels, Supported video modes: 1080p. LED type: IR. Width: 88 mm, Depth: 36.1 mm, Height: 177.4 mm

## Merkmale

Packaging data		Weight & dimensions	
Outdoor unit included	Y	Width	88 mm
		Depth	36.1 mm
		Height	177.4 mm
Management features		Design	
Web-based management	Y	Product colour	Aluminium

Syslog	Y	International Protection (IP) code	IP67
		IK code	IK07
		Housing material	Aluminium
		Control type	Buttons
		Proper use	Outdoor

Night vision

Night vision	Y
LED type	IR

Network

Ethernet interface type	Fast Ethernet
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Y

Operational conditions

Operating temperature (T-T)	-40 - 70 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-10 - 95% H)	

Camera

Megapixel (approx.)	2 MP
Maximum image resolution	1920 x 1080 pixels
Supported video modes	1080p
Sensor type	CMOS
Optical sensor size	30.5 / 9 mm (1.2 / 9")
Viewing angle, horizontal	120°
Viewing angle, vertical	60°

Technical details

Connectivity technology	Wired
Colour	Y
Speakerphone	Y
Memory card slot	Y
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	128 GB
Voice codecs	G.722
Motion detection function	Y
Number of buttons	1 buttons
Backlight buttons	Y
RFID reader	Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.