

Fanvil i62 video intercom system



Artikel	128497
Herstellernummer	I62
EAN	6937295602913
Fanvil	

Based on SIP and ONVIF protocols, i62 is a video door phone that integrates powerful functionalities of access control, intercom, and security protection. Featuring an aluminum alloy design and single speed-dial button, i62 delivers a high-quality elegant appearance. With high protection level IP66 and IK07, it is waterproof, dustproof and anti-collision in most outdoor environments. i62 allows users to make audio/video calls via a speed-dial button and a 2 Mega-pixel camera and achieve access control by different modes. With rich input and output interfaces, i62 is easy to link with other security devices and customize into various solutions in apartments, commercial buildings, communities and industrial parks.

Zusammenfassung

Based on SIP and ONVIF protocols, i62 is a video door phone that integrates powerful functionalities of access control, intercom, and security protection. Featuring an aluminum alloy design and single speed-dial button, i62 delivers a high-quality elegant appearance. With high protection level IP66 and IK07, it is waterproof, dustproof and anti-collision in most outdoor environments. i62 allows users to make audio/video calls via a speed-dial button and a 2 Mega-pixel camera and achieve access control by different modes. With rich input and output interfaces, i62 is easy to link with other security devices and customize into various solutions in apartments, commercial buildings, communities and industrial parks.

Fanvil i62, 2 MP, 1920 x 1080 pixels, 1080p, CMOS, 30.5 / 9 mm (1.2 / 9"), 120°

Fanvil i62. Megapixel (approx.): 2 MP, Maximum image resolution: 1920 x 1080 pixels, Supported video modes: 1080p. LED type: IR. Voice codecs: G.722. Product colour: Aluminium, International Protection (IP) code: IP67, IK code: IK07. Compatible memory cards: MicroSD (TransFlash), Maximum memory card size: 128 GB

Merkmale

Audio		Storage	
Voice codecs		Memory card slot	Yes
		Compatible memory cards	MicroSD (TransFlash)
		Maximum memory card size	128 GB
Packaging data		Weight & dimensions	
Outdoor unit included	Yes	Width	88 mm

Depth	36.1 mm
Height	177.4 mm

Management features

Web-based management	Yes
Syslog	Yes

Night vision

Night vision	Yes
LED type	IR

Network

Ethernet interface type	Fast Ethernet
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Yes

Operational conditions

Operating temperature (T-T)	-40 - 70 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-10 - 95% H)	

Design

Product colour	Aluminium
International Protection (IP) code	IP67
IK code	IK07
Housing material	Aluminium
Control type	Buttons
Proper use	Outdoor

Camera

Megapixel (approx.)	2 MP
Maximum image resolution	1920 x 1080 pixels
Supported video modes	1080p
Sensor type	CMOS
Optical sensor size	30.5 / 9 mm (1.2 / 9")
Viewing angle, horizontal	120°
Viewing angle, vertical	60°

Technical details

Connectivity technology	Wired
Colour	Yes
Speakerphone	Yes
Motion detection function	Yes
Number of buttons	1 buttons
Backlight buttons	Yes
RFID reader	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.