# HP E24m G4 computer monitor

| | |
|---|---|
| **Artikel** | 129371 |
| **Herstellernummer** | 40Z32AA#ABB |
| **EAN** | 0195908730736 |
| HP | |

Connect with Confidence. Conference with Ease.
Conference and connect with ease with the Zoom Certified HP E24m G4 USB-C Conferencing Monitor that has an integrated 5MP, tilt-adjustable webcam, front-firing speakers, and dual mics. Work effortlessly and simplify your set up with one USB-C® cable[1] that delivers data, video, and up to 65W of laptop charging.

## Zusammenfassung

Connect with Confidence. Conference with Ease.
Conference and connect with ease with the Zoom Certified HP E24m G4 USB-C Conferencing Monitor that has an integrated 5MP, tilt-adjustable webcam, front-firing speakers, and dual mics. Work effortlessly and simplify your set up with one USB-C® cable[1] that delivers data, video, and up to 65W of laptop charging.

HP E24m G4, 60.5 cm (23.8"), 1920 x 1080 pixels, Full HD, 5 ms, Black, Silver

HP E24m G4. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black, Silver

## Merkmale

### Logistics data

| | |
|---|---|
| Harmonized System (HS) code | 85285210 |

### Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 5 - 35 °C |
| Operating relative humidity (H-H) | 20 - 80% |

### Multimedia

| | |
|---|---|
| Built-in speaker(s) | Yes |
| Built-in camera | Yes |
| Number of speakers | 2 |
| Megapixel (approx.) | 5 MP |
| Built-in microphone | Yes |

### Weight & dimensions

| | |
|---|---|
| Width (with stand) | 53.9 mm |
| Depth (with stand) | 53.1 mm |
| Height (with stand) | 21.6 mm |

## Sustainability

| | |
|---|---|
| Sustainability certificates | ENERGY STAR |
| Sustainable technologies and materials | Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Contains Ocean-Bound plastic |

## Performance

| | |
|---|---|
| Flicker-free technology | Yes |
| Low Blue Light technology | Yes |
| HP segment | Business |

## Other features

| | |
|---|---|
| Weight | 7.39 kg |
| Height | 355.6 mm |
| Width | 539.4 mm |
| Depth | 47 mm |

## Packaging data

| | |
|---|---|
| Package width | 539.4 mm |
| Package depth | 216 mm |
| Package height | 530.7 mm |
| Package weight | 10.3 kg |

## Design

| | |
|---|---|
| Market positioning | Business |
| Product colour | Black, Silver |
| Detachable stand | Yes |
| Country of origin | China |
| Certification | Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CEL Grade 1; cTUVus; EAC; ENERGY STAR®; E-standby; FCC; ISO 9241-307; KC/KCC; NOM; PSB; RCM; SEPA; TCO Certified; TCO Certified Edge; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Mexico Energy; ICE; UAE; TGM; TUV-GS; Ukraine certificates; NRCS of South Africa; Belarus Energy |

| | |
|---|---|
| Weight (with stand) | 7.39 kg |
| Width (without stand) | 539.4 mm |
| Depth (without stand) | 4.7 mm |
| Height (without stand) | 35.6 mm |

## Power

| | |
|---|---|
| Energy efficiency class (SDR) | F |
| Energy consumption (SDR) per 1000 hours | 18 kWh |
| Power consumption (typical) | 3.7 W |
| Power consumption (standby) | 0.5 W |
| Power consumption (max) | 150 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |
| Power supply type | Internal |
| Energy efficiency scale | A to G |

## Ergonomics

| | |
|---|---|
| VESA mounting | Yes |
| Panel mounting interface | 100 x 100 mm |
| Cable lock slot | Yes |
| Height adjustment | Yes |
| Height adjustment | 15 cm |
| Pivot | Yes |
| Pivot angle | -90 - 90° |
| Swivelling | Yes |
| Swivel angle range | -45 - 45° |
| Tilt angle range | -5 - 23° |
| Tilt adjustment | Yes |

## Ports & interfaces

| | |
|---|---|
| USB Type-A downstream ports quantity | 4 |
| USB Power Delivery up to | 65 W |
| HDMI | Yes |
| HDMI ports quantity | 1 |
| HDMI version | 1.4 |
| DisplayPorts quantity | 2 |
| DisplayPort version | 1.2 |
| Audio input | Yes |
| Audio output | Yes |
| Headphone connectivity | 3.5 mm |
| HDCP | Yes |

## Display

| | |
|---|---|
| Display diagonal | 60.5 cm (23.8") |
| Display resolution | 1920 x 1080 pixels |
| HD type | Full HD |
| Native aspect ratio | 16:9 |
| Panel type | IPS |
| Backlight type | Edge LED |
| Touchscreen | No |
| Display brightness (typical) | 300 cd/m² |
| Response time | 5 ms |
| Anti-glare screen | Yes |
| Screen shape | Flat |
| Supported graphics resolutions | 640 x 480 (VGA), 720 x 400, 800 |

| | |
|---|---|
| | x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1440 x 900 (WXGA+), 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080) |
| Contrast ratio (typical) | 1000:1 |
| Contrast ratio (dynamic) | 10000000:1 |
| Maximum refresh rate | 75 Hz |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours | 16.7 million colours |
| Pixel pitch | 0.2745 x 0.2745 mm |
| Pixel density | 93 ppi |
| Digital horizontal frequency | 30 - 85 kHz |
| Digital vertical frequency | 50 - 75 Hz |
| Display diagonal (metric) | 60.45 cm |
| Surface hardness | 3H |
| Colour depth | 8 bit |
| RGB colour space | sRGB |
| Colour gamut | 99% |