# iiyama ProLite computer monitor



Artikel Herstellernummer EAN iivama 129416 XUB2792QSC-B5 4948570121663

27" WQHD IPS panel with an ergonomic stand and USB-C Connectivity

Supplying USB Type-C connectivity, the XUB2792QSC allows you to simplify your workspace by using a single cable to connect, power (65W power delivery) and charge the notebook from the monitor, providing the foundation for hybrid office spaces. The IPS panel and WQHD (2560x1440) resolution offer noticeably shaper images, excellent colour performance, wide viewing angles, making this ideal for productivity solutions, demanding office applications as well as CAD. Equipped with speakers, headphone socket, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort.

TCO conformity and low power consumption make this XUB2792QSC an ideal display for the modern environmentally conscious, yet productive workplace.

#### **IPS TECHNOLOGY**

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

#### USB-C

With one wire you can charge your laptop, connect video (DP-alt mode) and connect with your peripherals through the build in USB 3.0 HUB.

#### **IPS TECHNOLOGY**

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

#### WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

#### FLICKER-FREE + BLUE LIGHT

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.

#### SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

## Zusammenfassung

27" WQHD IPS panel with an ergonomic stand and USB-C Connectivity

Supplying USB Type-C connectivity, the XUB2792QSC allows you to simplify your workspace by using a single cable to connect, power (65W power delivery) and charge the notebook from the monitor, providing the foundation for hybrid office spaces. The IPS panel and WQHD (2560x1440) resolution offer noticeably shaper images, excellent colour performance, wide viewing angles, making this ideal for productivity solutions, demanding office applications as well as CAD. Equipped with speakers, headphone socket, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort.

TCO conformity and low power consumption make this XUB2792QSC an ideal display for the modern environmentally conscious, yet productive workplace.

#### **IPS TECHNOLOGY**

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

#### USB-C

With one wire you can charge your laptop, connect video (DP-alt mode) and connect with your peripherals through the build in USB 3.0 HUB.

#### **IPS TECHNOLOGY**

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

#### WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

#### FLICKER-FREE + BLUE LIGHT

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.

#### **SPEAKERS**

This LED monitor is equipped with two high quality stereo speakers.

iiyama ProLite, 68.6 cm (27"), 2560 x 1440 pixels, Wide Quad HD, LED, 4 ms, Black

iiyama ProLite . Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Wide Quad HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black

## Merkmale

		Weight & dimensions	
Design		Width (with stand)	613.5 mm
		Depth (with stand)	209.5 mm
Market positioning	Business	Height (with stand)	544.5 mm
Product colour	Black	Weight (with stand)	6.8 kg
		Width (without stand)	613.5 mm
		Depth (without stand)	54 mm
Performance		Height (without stand)	371 mm
Flicker-free technology	Y		
Low Blue Light technology	Y	Ports & interfaces	
		Built-in USB hub	Y
Sustainability		USB Power Delivery	Υ
		USB Power Delivery up to	65 W
Sustainability compliance	Υ	HDMI	Υ
Sustainability certificates	CE, ENERGY STAR, ErP, REACH, RoHS, UKCA	HDMI ports quantity	1
		DisplayPorts quantity	1
		Headphone out	Y
		HDCP	Υ

#### Multimedia

Built-in speaker(s)	Y	
Number of speakers	2	
RMS rated power	4 W	

## Packaging content

Stand included	Υ
Cables included	AC, DisplayPort, HDMI, USB Type-C
Quick start guide	Y

## Packaging data

Package width	693 mm
Package depth	170 mm
Package height	446 mm
Package weight	8.4 kg
Package type	Box

### Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	22 kWh
Power consumption (typical)	21 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

## Ergonomics

VESA mounting	Y
Panel mounting interface	100 x 100 mm
Wall mountable	Y
Cable management	Y
Cable lock slot	Y
Cable lock slot type	Kensington
Height adjustment	Y
Height adjustment	15 cm
Pivot	Y
Pivot angle	0 - 90°
Swivelling	Y
Swivel angle range	45 - 90°
Tilt angle range	5 - 23°
On Screen Display (OSD)	Y
On Screen Display (OSD)	Czech, German, Dutch, English,
languages	Spanish, French, Italian,
	Japanese, Polish
Number of OSD languages	9

# Display

Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
HD type	Wide Quad HD
Native aspect ratio	16:9
Display technology	LED
Panel type	IPS
Display brightness (typical)	350 cd/m <sup>2</sup>
Response time	4 ms
Display surface	Matt
Screen shape	Flat
Supported graphics resolutions	2560 x 1440
Supported video modes	1440p
Aspect ratio	16:9
Contrast ratio (typical)	1000:1
Contrast ratio (dynamic)	8000000:1
Maximum refresh rate	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.7 million colours
Pixel pitch	0.233 x 0.233 mm
Horizontal scan range	30 - 120 kHz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.