

iiyama T2455MSC-B1 Signage Display



Artikel	130008
Herstellernummer	T2455MSC-B1
EAN	4948570118960
iiyama	

The ProLite T2455MSC with its Full HD (1920x1080) resolution and accurate PCAP 10 point touch technology, delivers a seamless and accurate touch response. Featuring IPS LCD screen technology, it offers exceptional colour performance and wide viewing angles. A special Nano coating ensures a smoother touch and less resistance in the swipe. It makes the screen less static and susceptible to dirt, dust and fingerprints. The built-in webcam and microphone make the T2455MSC also a complete solution for online communication. Its flexible stand can be positioned at several angles creating a comfortable and ergonomic user experience. A perfect choice for a vast array of applications.

Zusammenfassung

The ProLite T2455MSC with its Full HD (1920x1080) resolution and accurate PCAP 10 point touch technology, delivers a seamless and accurate touch response. Featuring IPS LCD screen technology, it offers exceptional colour performance and wide viewing angles. A special Nano coating ensures a smoother touch and less resistance in the swipe. It makes the screen less static and susceptible to dirt, dust and fingerprints. The built-in webcam and microphone make the T2455MSC also a complete solution for online communication. Its flexible stand can be positioned at several angles creating a comfortable and ergonomic user experience. A perfect choice for a vast array of applications.

iiyama T2455MSC-B1, Digital signage flat panel, 61 cm (24"), LED, 1920 x 1080 pixels

iiyama T2455MSC-B1. Product design: Digital signage flat panel. Display diagonal: 61 cm (24"), Display technology: LED, Display resolution: 1920 x 1080 pixels, Display brightness: 400 cd/m², HD type: Full HD, Touchscreen. Product colour: Black

Merkmale

Technical details

Sustainability certificates RoHS, WEEE

Features

Base colour Black
Base material Metal

Ports & interfaces

HDMI ports quantity	1
DVI port	N
DisplayPorts quantity	1
USB port	Y
USB ports quantity	2
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)

Design

Audio

Built-in speaker(s)	Y
Number of built-in speakers	2
RMS rated power	1 W

Performance

Purpose	Commercial
On Screen Display (OSD)	Y
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian

Weight & dimensions

Display width	566 mm
Display depth	43.5 mm
Display height	337.5 mm
Display weight	4.4 kg

Product design	Digital signage flat panel
Placement supported	Indoor
Orientation	Horizontal
Product colour	Black
VESA mounting	Y
Panel mounting interface	100 x 100 mm
Anti-glare screen	Y
Fingerprint resistant	Y

Power

Power consumption (typical)	18 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	15 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Display

Panel type	IPS
LED backlighting type	Direct-LED
Display diagonal	61 cm (24")
Display technology	LED
Display resolution	1920 x 1080 pixels
Display brightness	400 cd/m ²
HD type	Full HD
Touchscreen	Y
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Native aspect ratio	16:9
Response time	5 ms
Contrast ratio (typical)	1000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.78 million colours
Pixel pitch	0.274 x 0.274 mm
Active display area (W x H)	527 x 296 mm
Display diagonal (metric)	60.5 cm
Number of displays	1
Horizontal scan range	30 - 83 kHz
Surface hardness	7H

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.