

Ubiquiti G5 Professional



Artikel	131747
Herstellernummer	UVC-G5-PRO
EAN	0810084690246
Ubiquiti	

Indoor/outdoor 4K PoE Camera with exceptional image performance and 3x optical zoom lens.

Zusammenfassung

Indoor/outdoor 4K PoE Camera with exceptional image performance and 3x optical zoom lens.

Ubiquiti G5 Professional, IP security camera, Indoor & outdoor, Wired, FCC, IC, CE, Ceiling/Wall/Pole, White

Ubiquiti G5 Professional. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 35, 109.9°, Lens viewing angle, vertical: 19.8, 60°, Lens viewing angle, diagonal: 40, 127.7°. Optical sensor size: 25.4 / 2 mm (1 / 2"). Optical zoom: 3x, Focal length range: 4.1 - 12.3 mm

Merkmale

Audio

Built-in microphone	Y
---------------------	---

Image sensor

Optical sensor size	25.4 / 2 mm (1 / 2")
---------------------	----------------------

Management features

Reset button	Y
--------------	---

Ports & interfaces

Packaging content

Number of cameras	1
Mounting kit	Y
Manual	Y

Power

Power source type	PoE
Power consumption (max)	10 W
DC output voltage	37, 48, 54, 57

Weight & dimensions

Diameter	8.6 cm
Length	154.3 mm
Weight	650 g

Ethernet LAN (RJ-45) ports 1

Storage

Built-in HDD N

Operational conditions

Operating temperature (T-T) -20 - 50 °C

Operating relative humidity (H-0 - 90%
H)

Camera

Lens viewing angle, horizontal 35, 109.9°

Lens viewing angle, vertical 19.8, 60°

Lens viewing angle, diagonal 40, 127.7°

Night vision

Night vision Y

Night vision distance 25 m

LED type IR

Network

Ethernet LAN	Y
Ethernet interface type	Fast Ethernet
Wi-Fi	N
Bluetooth	N

Lens system

Zoom capability	Y
Optical zoom	3x
Maximum aperture number	3.3
Minimum aperture number	1.53
Focal length range	4.1 - 12.3 mm

Performance

Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Built-in processor	Y
Infrared (IR) cut-off filter	Y
Certification	FCC, IC, CE

Design

Form factor	Bullet
Mounting type	Ceiling/Wall/Pole
Product colour	White
Housing material	Aluminium, Polycarbonate (PC)
International Protection (IP) code	IP65
IK code	IK04
Weatherproof	Y

Video

Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264
Frame rate	30 fps
Noise reduction	Y
Noise reduction technology	2D noise reduction, 3D noise reduction
Image quality adjustment	Brightness, Contrast, Sharpness

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.