Acer X1526HK data projector



Artikel
Herstellernummer
EAN
Acer

132286 MR.JV611.001 4711121000379

Transform your home entertainment with vibrant, FHD images and a wide array of color enhancing technologies such as ColorBoost3D and ColorSafe II. With up to 4,000 lumens brightness, and a low input lag, it is the ideal projector for occasional game, movie or any other type of media on your list.

FHD Resolution

A 100" image of pure beauty in 1080p Full HD looks so real, you'll swear you're looking out the window.

4,000 Lumens Brightness

See crystal-clear, vibrant images from a distance in daylight or medium to large rooms with up to 4,000 lumens of brightness.

Image Shift

Project with precision and avoid setup problems. Using Image Shift and digital zoom, you can shift the image precisely to fit your screen without having to alter the existing mounting location.

Low Input Lag

Enjoy responsive control whether playing racing, sports or action games with an ultra-low latency that reduces frame delay to an incredible 16.7ms.

Acer BlueLightShield™

Protect your eyes from unnecessary strain by utilising Acer BlueLightShield™ technology.

Acer LumiSense™

Acer LumiSense™ adjusts the image brightness and colour saturation based on the content you're viewing.

Acer ColorBoost3D™

Reproduce lifelike colours and brilliantly bright images with Acer ColorBoost3D™ technology.

Keystone Correction for Distortion

Finding the right angle for your presentation is easier with auto keystone correction, which corrects vertical distortion.

Wireless Projection

Break free from the clutter of wires with easy wireless projection1 options and wireless dongle design.

Zusammenfassung

Transform your home entertainment with vibrant, FHD images and a wide array of color enhancing technologies such as ColorBoost3D and ColorSafe II. With up to 4,000 lumens brightness, and a low input lag, it is the ideal projector for occasional game, movie or any

other type of media on your list.

FHD Resolution

A 100" image of pure beauty in 1080p Full HD looks so real, you'll swear you're looking out the window.

4,000 Lumens Brightness

See crystal-clear, vibrant images from a distance in daylight or medium to large rooms with up to 4,000 lumens of brightness.

Image Shift

Project with precision and avoid setup problems. Using Image Shift and digital zoom, you can shift the image precisely to fit your screen without having to alter the existing mounting location.

Low Input Lag

Enjoy responsive control whether playing racing, sports or action games with an ultra-low latency that reduces frame delay to an incredible 16.7ms.

Acer BlueLightShield™

Protect your eyes from unnecessary strain by utilising Acer BlueLightShield™ technology.

Acer LumiSense™

Acer LumiSense™ adjusts the image brightness and colour saturation based on the content you're viewing.

Acer ColorBoost3D™

Reproduce lifelike colours and brilliantly bright images with Acer ColorBoost3D™ technology.

Keystone Correction for Distortion

Finding the right angle for your presentation is easier with auto keystone correction, which corrects vertical distortion.

Wireless Projection

Break free from the clutter of wires with easy wireless projection1 options and wireless dongle design.

Acer X1526HK, 4000 ANSI lumens, DLP, 1080p (1920x1080), 10000:1, 16:9, 4:3, 16:9

Acer X1526HK. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Lamp, Service life of light source: 4000 h, Service life of light source (economic mode): 10000 h. Focal length range: 15.85 - 17.44 mm, Aperture range (F-F): 2 - 2.05, Throw ratio: 1.5 - 1.65. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA). Serial interface type: RS-232

Merkmale

		Features	
Display		Interactive	N
		Noise level (economic mode)	26 dB
Built-in display	N	Projection modes	Ceiling, Front, Rear
		Noise level	32 dB
Logistics data			
Quantity per pack	1 pc(s)	Lens system	
		Focal length range	15.85 - 17.44 mm
		Aperture range (F-F)	2 - 2.05
Operational conditions		Zoom capability	Υ
		Throw ratio	1.5 - 1.65
Operating temperature (T-T)	0 - 40 °C		
Storogo		Packaging content	
Storage		Remote control included	Υ
Card reader integrated	N	Batteries included	Y
ca. a . bado. miogratod		Cables included	AC
		Manual	Y

Network

Smart TV	N
Ethernet LAN	N

Multimedia

Built-in speaker(s)	Υ
RMS rated power	3 W
Number of built-in speakers	1

Power

Power source	AC
Power consumption (typical)	290 W
AC input voltage	120 - 230 V

Design

Market positioning	Business
Product type	Standard throw projector
Product colour	White
Placement	Ceiling

Video

Analog signal format system	NTSC, PAL, SECAM
Full HD	Υ
3D	N
Supported graphics resolutions	1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)

Weight & dimensions

Width	322 mm
Depth	225 mm
Height	91 mm
Weight	2.6 kg

Light source

Light source type	Lamp
Service life of light source	4000 h
Service life of light source	10000 h
(economic mode)	
Lamp type	OSRAM
Lamp power	245 W
Lamps quantity	1 lamp(s)

Ports & interfaces

USB 2.0 ports quantity	1	
Audio (L/R) in	1	
Audio (L/R) out	1	
Serial interface type	RS-232	
HDMI ports quantity	2	
DVI port	N	
Mobile High-Definition Link (MHL)N		

Projector

Supported aspect ratios	4:3, 16:9
Projection distance	1 - 10 m
Projector brightness	4000 ANSI lumens
Projection technology	DLP
Projector native resolution	1080p (1920x1080)
Contrast ratio (typical)	10000:1
Native aspect ratio	16:9
Number of colours	1.07 billion colours
Horizontal scan range	15 - 100 kHz
Vertical scan range	24 - 120 Hz
Keystone correction, vertical	-40 - 40°

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.