# Seagate IronWolf Pro ST22000NT001 internal hard drive



Artikel Herstellernummer EAN Seagate 132340 ST22000NT001 8719706432269

IronWolf® Pro drives are engineered to deliver 24×7 performance, reliability, and dependability in multi-bay, multi-user commercial and enterprise RAID storage solutions. Total peace of mind with five-year limited warranty, complimentary three-year Rescue Data Recovery Services, and IronWolf Health Management.

#### IronWolf Pro

Always on, always accessible, all-CMR portfolio engineered to deliver 24×7 performance, reliability, and dependability in multi-bay, multi-user commercial and enterprise RAID storage solutions.

#### **Drive Health and Data Recovery**

IronWolf Health Management, helps protect data with prevention, intervention, and recovery recommendations to secure peak system health. Three years of complimentary Rescue Data Recovery Services are included with all IronWolf drives, so users don't incur high recovery costs. In-house secure facilities, with an industry-leading 95% success rate, enable data recovery after accidental data corruption or drive damage.

### Zusammenfassung

IronWolf® Pro drives are engineered to deliver 24×7 performance, reliability, and dependability in multi-bay, multi-user commercial and enterprise RAID storage solutions. Total peace of mind with five-year limited warranty, complimentary three-year Rescue Data Recovery Services, and IronWolf Health Management.

#### IronWolf Pro

Always on, always accessible, all-CMR portfolio engineered to deliver 24×7 performance, reliability, and dependability in multi-bay, multi-user commercial and enterprise RAID storage solutions.

#### **Drive Health and Data Recovery**

IronWolf Health Management, helps protect data with prevention, intervention, and recovery recommendations to secure peak system health. Three years of complimentary Rescue Data Recovery Services are included with all IronWolf drives, so users don't incur high recovery costs. In-house secure facilities, with an industry-leading 95% success rate, enable data recovery after accidental data corruption or drive damage.

Seagate IronWolf Pro ST22000NT001, 3.5", 22 TB, 7200 RPM

Seagate IronWolf Pro ST22000NT001. HDD size: 3.5", HDD capacity: 22 TB, HDD speed: 7200 RPM

## Merkmale

### Logistics data

Master (outer) cases per 20 pc(s) pallet

### Packaging data

Quantity

### Weight & dimensions

Width	101.8 mm
Height	26.1 mm
Depth	147 mm
Weight	690 g

1

### **Operational conditions**

Operating temperature (T-T)	0 - 65 °C
Storage temperature (T-T)	-40 - 70 °C
Non-operating vibration	2.27 G
Operating shock	40 G
Non-operating shock	200 G

#### Power

Power consumption (typical)	7.9 W
Power consumption (standby)	1.2 W
Power consumption (idle)	6 W
Operating voltage	5 / 12 V
Start-up current	2 A

#### Features

HDD size3.5"HDD capacity22 TBHDD speed7200 RPMInterfaceSerial ATA IIITypeHDDComponent forServer/workstationStorage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read(UBER)20 dBNoise level (idle)20 dBMean time between failures2500000 h		
HDD speed7200 RPMInterfaceSerial ATA IIITypeHDDComponent forServer/workstationStorage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	HDD size	3.5"
InterfaceSerial ATA IIITypeHDDComponent forServer/workstationStorage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	HDD capacity	22 TB
TypeHDDComponent forServer/workstationStorage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	HDD speed	7200 RPM
Component forServer/workstationStorage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	Interface	Serial ATA III
Storage drive buffer size512 MBHDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate<1 per 10^15 bits read	Туре	HDD
HDD interface transfer rate6 Gbit/sHDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	Component for	Server/workstation
HDD sustained transfer rate285 MiB/sUncorrectable Bit Error Rate< 1 per 10^15 bits read	Storage drive buffer size	512 MB
Uncorrectable Bit Error Rate (UBER)< 1 per 10^15 bits readRotational Vibration (RV) sensors YesNoise level (idle)20 dBMean time between failures2500000 h	HDD interface transfer rate	6 Gbit/s
(UBER)Rotational Vibration (RV) sensors YesNoise level (idle)20 dBMean time between failures2500000 h	HDD sustained transfer rate	285 MiB/s
Rotational Vibration (RV) sensors YesNoise level (idle)20 dBMean time between failures2500000 h	Uncorrectable Bit Error Rate	< 1 per 10^15 bits read
Noise level (idle)20 dBMean time between failures2500000 h	(UBER)	
Mean time between failures 2500000 h	Rotational Vibration (RV) sensors Yes	
	Noise level (idle)	20 dB
(MTBF)	Mean time between failures	2500000 h
(	(MTBF)	

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.