

Xilence XP650R6.2 power supply unit



Artikel	132490
Herstellernummer	XN420
EAN	4044953503535
Xilence	

The C+Series is a power supply series with the ATX standard 2.52 and black ribbon cables. The power supplies are designed for office and home computers, but can also be installed in PCs that are occasionally used for gaming. The black design of the power supplies and the elegant flat ribbon cables blend visually into any PC build. The power supplies deliver stable voltages with high efficiency (80+ Standard) to meet the ErP2014 standard. The integrated black 120mm fan provides silent cooling. Four integrated safety circuits ensure safe operation at all times.

Zusammenfassung

The C+Series is a power supply series with the ATX standard 2.52 and black ribbon cables. The power supplies are designed for office and home computers, but can also be installed in PCs that are occasionally used for gaming. The black design of the power supplies and the elegant flat ribbon cables blend visually into any PC build. The power supplies deliver stable voltages with high efficiency (80+ Standard) to meet the ErP2014 standard. The integrated black 120mm fan provides silent cooling. Four integrated safety circuits ensure safe operation at all times.

Xilence XP650R6.2, 650 W, 200 - 240 V, 50 Hz, 10 A, Active, 23 A

Xilence XP650R6.2. Total power: 650 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm

Merkmale

Design

Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)

Performance

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Motherboard power cable length	50 cm
Number of SATA power connectors	5
Number of PATA power connectors	3
PCI Express power connectors (6+2 pin)	2

80 PLUS certification	80 PLUS Gold
Purpose	PC
Power supply unit (PSU) form factor	ATX
Bearing technology	Hypro Bearing

Power

Total power	650 W
AC input voltage	200 - 240 V
AC input frequency	50 Hz
Input current	10 A
Power Factor Correction (PFC) type	Active
Max output current (+3.3V)	23 A
Max output current (+12V1)	48 A
Max output current (+5V)	17 A
Max output current (-12V)	0.5 A
Max output current (+5Vsb)	2.5 A
Efficiency	82%
Power protection features	Over voltage, Overload, Short circuit, Under voltage

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.