iiyama ProLite XU2492HSU-B6 computer monitor



Artikel Herstellernummer EAN iivama 133746 XU2492HSU-B6 4948570122585

24" IPS technology panel with USB hub and 100Hz refresh rate

Stylish edge-to-edge design makes the ProLite XU2492HSU perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. The 100Hz refresh rate together with FreeSync function provides an instant, tangible improvement in image smoothness. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, 2 port USB 3.2 hub, headphone socket, HDMI and DisplayPort connections, plus a blue light reducer function to reduce eye fatigue for optimal user comfort, make this 24" monitor a great choice for both multi-monitor configuration and office applications.

IPS TECHNOLOGY

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

100HZ

A 100Hz refresh rate translates into increased smoothness of the image. This means that flickering is reduced and therefore eye fatigue is also less noticeable. The increased frequency also means smoother transitions between contrasting colours, smoother motion scenes in both movies and gaming, and even reduced mouse cursor flickering.

SLIM LINE

Slim Line monitors feature a sleek bezel and are therefore particularly suitable for video wall or a multi-monitor set-up.

FLICKER-FREE + BLUE LIGHT

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.

SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

Zusammenfassung

24" IPS technology panel with USB hub and 100Hz refresh rate

Stylish edge-to-edge design makes the ProLite XU2492HSU perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. The 100Hz refresh rate together with FreeSync function provides an instant, tangible improvement in image smoothness. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, 2 port USB 3.2 hub, headphone socket, HDMI and DisplayPort connections, plus a blue light reducer function to reduce eye fatigue for optimal user comfort, make this 24" monitor a

great choice for both multi-monitor configuration and office applications.

IPS TECHNOLOGY

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

100HZ

A 100Hz refresh rate translates into increased smoothness of the image. This means that flickering is reduced and therefore eye fatigue is also less noticeable. The increased frequency also means smoother transitions between contrasting colours, smoother motion scenes in both movies and gaming, and even reduced mouse cursor flickering.

SLIM LINE

Slim Line monitors feature a sleek bezel and are therefore particularly suitable for video wall or a multi-monitor set-up.

FLICKER-FREE + BLUE LIGHT

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.

SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

iiyama ProLite XU2492HSU-B6, 60.5 cm (23.8"), 1920 x 1080 pixels, Full HD, LED, Black

iiyama ProLite XU2492HSU-B6. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black

Merkmale

		Performance	
Other features		NVIDIA G-SYNC	No
Certification	TCO Certified, CE, TÜV-	AMD FreeSync	Yes
Certification	Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA	AMD FreeSync type	FreeSync
		Flicker-free technology	Yes
		Low Blue Light technology	Yes
Design		Ergonomics	
-		VESA mounting	Yes
Market positioning	Home	Panel mounting interface	100 x 100 mm
Product colour	Black	Cable management	Yes
		Cable lock slot	No
		Height adjustment	No
Packaging content		Tilt angle range	2 - 22°
3 3 1 1		On Screen Display (OSD)	Czech, German, English,
Cables included	DisplayPort, HDMI, Power,	languages	Spanish, French, Italian,
	USB		Japanese, Polish, Russian
Quick start guide	Yes		
Multimedia		Ports & interfaces	
Martimeara		Built-in USB hub	Yes
Number of speakers	2	USB hub version	3.2 Gen 1 (3.1 Gen 1)
RMS rated power	2 W	USB Type-A downstream ports	4
Built-in speaker(s)	Yes	quantity	
Built-in camera	No	HDMI	Yes
		HDMI ports quantity	1
		DisplayPorts quantity	1
Packaging data		Headphone out	Yes
i aonaging aata		Headphone outputs	1

Headphone outputs

HDCP

1

Yes

Package width

610 mm

Package depth	130 mm
Package height	410 mm
Package weight	4.9 kg

Weight & dimensions

Width (with stand)	539.5 mm
Depth (with stand)	199.5 mm
Height (with stand)	415 mm
Weight (with stand)	3.4 kg

Power

Energy efficiency class (SDR) D Energy efficiency class (HDR) Not available Energy consumption (SDR) per 13.2 kWh 1000 hours Power consumption (typical) 0 W Power consumption (standby) 0.5 W Power consumption (off) 0.3 W AC input voltage 100 - 240 V AC input frequency 50/60 Hz European Product Registry for 1671458 Energy Labelling (EPREL) code

Display

Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Display technology	LED
Panel type	IPS
Touchscreen	No
Display brightness (typical)	250 cd/m ²
Response time (MPRT)	0.4 ms
Screen shape	Flat
Contrast ratio (typical)	1300:1
Contrast ratio (dynamic)	8000000:1
Maximum refresh rate	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.7 million colours
Response time (fast)	0.4 ms
Pixel pitch	0.275 x 0.275 mm
Horizontal scan range	30 - 115 kHz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.