

# iiyama ProLite XUB2797HSN-W2 computer monitor



**Artikel**  
**Herstellernummer**  
**EAN**  
iiyama

139513  
XUB2797HSN-W2  
4948570124992

Equipped with a USB-C dock connector, the XUB2797HSN allows you to simplify your workspace by using a single cable to both send signal from your notebook to your monitor and power and charge the notebook from the monitor. Additionally, if your monitor is connected to the Internet with a LAN cable, your notebook will automatically be connected to the network as well. Thanks to a DisplayPort output you can easily extend your desktop by creating a double-monitor set-up. Supplied with a 150mm height-adjustable stand featuring pivot and swivel functions, the XUB2797HSN allows you to easily adjust the screen position to your preferences. Available also without USB-C dock: XUB2797QSU-W2 .

## Zusammenfassung

Equipped with a USB-C dock connector, the XUB2797HSN allows you to simplify your workspace by using a single cable to both send signal from your notebook to your monitor and power and charge the notebook from the monitor. Additionally, if your monitor is connected to the Internet with a LAN cable, your notebook will automatically be connected to the network as well. Thanks to a DisplayPort output you can easily extend your desktop by creating a double-monitor set-up. Supplied with a 150mm height-adjustable stand featuring pivot and swivel functions, the XUB2797HSN allows you to easily adjust the screen position to your preferences. Available also without USB-C dock: XUB2797QSU-W2 .

iiyama ProLite 27" IPS technology panel with USB-C dock and RJ45 (LAN), 68.6 cm (27"), 1920 x 1080 pixels, Full HD, LED, 1 ms, White

iiyama ProLite 27" IPS technology panel with USB-C dock and RJ45 (LAN). Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: White

## Merkmale

### Network

Ethernet LAN Yes

### Other features

### Weight & dimensions

Width (with stand)	611.5 mm
Depth (with stand)	209.5 mm
Height (with stand)	550.5 mm
Weight (with stand)	6 kg
Width (without stand)	611.5 mm
Depth (without stand)	209.5 mm

Warranty period	5 year(s)
-----------------	-----------

Height (without stand)	400.5 mm
------------------------	----------

## Design

Market positioning	Business
Product colour	White

## Performance

VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes

## Multimedia

Number of speakers	2
RMS rated power	4 W
Built-in speaker(s)	Yes
Built-in camera	No

## Packaging data

Package width	679 mm
Package depth	130 mm
Package height	427 mm
Package weight	8.7 kg

## Ports & interfaces

Built-in USB hub	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	65 W
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort out version	1.2
HDCP	Yes

## Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	22 kWh
Power consumption (typical)	22 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

## Ergonomics

VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	0 - 90°
Tilt adjustment	Yes
Tilt angle range	5 - 23°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Russian

## Display

Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Display technology	LED
Panel type	IPS
Touchscreen	No
Display brightness (typical)	300 cd/m <sup>2</sup>
Response time	1 ms
Response time (MPRT)	1 ms
Display surface	Matt
Screen shape	Flat

Contrast ratio (typical)	1000:1
Contrast ratio (dynamic)	80000000:1
Maximum refresh rate	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.7 million colours
Pixel pitch	0.311 x 0.311 mm
Horizontal scan range	30 - 110 kHz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	69 cm
DDC/CI	Yes
Colour gamut standard	NTSC, sRGB
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.