

be quiet! System Power 11 750W power supply unit



Artikel	141938
Herstellernummer	BP012EU
EAN	4260052191880
be quiet!	

Proven reliability, quiet operation

System Power 11 750W has been built with value-oriented users in mind that do not want to pass on reliability and quietness. Elaborated features such as ATX 3.1 compatibility and a temperature-controlled fan underline the value System Power 11 750W offers even at entry-level.

Zusammenfassung

Proven reliability, quiet operation

System Power 11 750W has been built with value-oriented users in mind that do not want to pass on reliability and quietness. Elaborated features such as ATX 3.1 compatibility and a temperature-controlled fan underline the value System Power 11 750W offers even at entry-level.

be quiet! System Power 11 750W, 750 W, 200 - 240 V, 50 Hz, 4 A, 120 W, 750 W

be quiet! System Power 11 750W. Total power: 750 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: CB, CE, RoHS, TÜV mark, UKCA, WEEE

Merkmale

Technical details

Sustainability certificates ENERGY STAR, ErP

Certificates

Waste Electrical and Electronic Equipment (WEEE) compliance Yes
Compliance certificates CB, CE, RoHS, TÜV mark,

Packaging data

Package width	195 mm
Package depth	268 mm
Package height	97 mm
Package weight	2.4 kg
Package type	Box

Design

Product colour	Black
Cooling type	Active

UKCA, WEEE

Fan diameter	12 cm
Number of fans	1 fan(s)
Fan speed	0 - 2100 RPM
On/off switch	Yes

Other features

Screws included	Yes
Cable ties included	Yes

Weight & dimensions

Width	150 mm
Depth	86 mm
Height	140 mm
Weight	2.04 kg

Logistics data

Shipping (inner) case length	55.6 cm
Shipping (inner) case width	31.1 cm
Shipping (inner) case height	21.8 cm
Products per shipping (inner) case	6 pc(s)
Shipping (inner) case gross weight	15.6 kg

Performance

80 PLUS certification	80 PLUS Bronze
Purpose	PC
Power supply unit (PSU) form factor	ATX
ATX version	3.1
EPS version	2.92
Noise level	33.4 dB
Bearing technology	Rifle
Mean time between failures (MTBF)	100000 h

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Number of SATA power connectors	6
Peripheral (Molex) power connectors (4-pin)	1
EPS power connector (8-pin)	Yes
PCI Express power connectors (6+2 pin)	3
PCI Express power connectors (12-pin)	1
CPU P4 connector (4-pin)	1
CPU power connector (4+4 pin)	Yes
Cabling type	Non-Modular

Power

Total power	750 W
AC input voltage	200 - 240 V
AC input frequency	50 Hz
Input current	4 A
Power factor	0.98
Number of +12V rail(s)	1
Combined power (+3.3V)	120 W
Combined power (+12V)	750 W
Combined power (+5V)	120 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V1)	62.5 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Hold time	17.34 ms
Efficiency	90%
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Surge & inrush, Under voltage