

OKI ML6300FB SC dot matrix printer



Artikel	185098
Herstellernummer	43490003
EAN	5031713045397
OKI	

A printer with essential credentials for front desk work, offering both reliability and assistance.

- Small footprint allows printer to be close at hand without getting in the way
- Flat bed design gives broad media handling capability, including card stock
- Multi-part paper handling (original + 5 copies) for greater efficiency and convenience
- Print speeds of up to 450 characters per second for faster transactions
- Clean hands ribbon changing ensures no delay, mess or hassle when fitting a new ribbon

With print speeds of up to 450 characters per second and multi-part copy capability, the ML6300FB provides unerring support for businesses that have a strong customer service/productivity emphasis. Its flat bed design and straight paper-path makes it ideal for printing on awkward media varying from light to heavy, including card stock.

Businesses most likely to benefit from the ML6300FB include hotels, banks, retail stores, or remote and even industrial offices that frequently deal with pre-printed forms, cheques, tickets, receipts and labels - both pre-cut and tractor fed. Additionally, the small footprint makes it the ideal choice for businesses where space is at a premium.

Zusammenfassung

A printer with essential credentials for front desk work, offering both reliability and assistance.

- Small footprint allows printer to be close at hand without getting in the way
- Flat bed design gives broad media handling capability, including card stock
- Multi-part paper handling (original + 5 copies) for greater efficiency and convenience
- Print speeds of up to 450 characters per second for faster transactions
- Clean hands ribbon changing ensures no delay, mess or hassle when fitting a new ribbon

With print speeds of up to 450 characters per second and multi-part copy capability, the ML6300FB provides unerring support for businesses that have a strong customer service/productivity emphasis. Its flat bed design and straight paper-path makes it ideal for printing on awkward media varying from light to heavy, including card stock.

Businesses most likely to benefit from the ML6300FB include hotels, banks, retail stores, or remote and even industrial offices that frequently deal with pre-printed forms, cheques, tickets, receipts and labels - both pre-cut and tractor fed. Additionally, the small footprint makes it the ideal choice for businesses where space is at a premium.

OKI ML6300FB SC, 450 cps, 360 x 360 DPI, 400 cps, 10,12,15,17,17.1,20 cpi, Manual, 64 KB

OKI ML6300FB SC. Maximum print speed: 450 cps, Maximum resolution: 360 x 360 DPI, Normal print speed: 400 cps. Paper feed: Manual. Buffer size: 64 KB, Sound pressure level (printing): 58 dB, Page description languages: Epson ESC/P2, IBM ProPrinter. Standard interfaces: Parallel, USB 2.0, Optional connectivity: Ethernet, Serial (RS-232). Print head: 24-pin, Print direction: Bidirectional, Print head life: 200 million characters

Merkmale

Paper handling		Operational conditions	
Paper feed	Manual	Operating temperature (T-T)	5 - 40 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	30 - 85%
		Storage relative humidity (H-H)	0 - 95%
System requirements		Other features	
Windows operating systems supported	Yes	Connectivity technology	Wired
		Print technology	Dot matrix
		Printing width	106 characters
		Fonts included	Courier, Roman, Swiss, Prestige, Gothic, Utility, Swiss Bold, Orator, OCR-A, OCR-B, HSD & Barcodes
Ports & interfaces		Weight & dimensions	
Standard interfaces	Parallel, USB 2.0	Width	425 mm
Optional connectivity	Ethernet, Serial (RS-232)	Depth	255 mm
		Height	210 mm
		Weight	7.5 kg
Power		Endurance	
AC input voltage	220-240 V	Print head	24-pin
AC input frequency	50 - 60 Hz	Print direction	Bidirectional
		Print head life	200 million characters
		Ribbon life	4 million characters
		Mean time between failures (MTBF)	12000 h
Features		Printing	
Buffer size	64 KB	Maximum resolution	360 x 360 DPI
Sound pressure level (printing)	58 dB	Colour	No
Page description languages	Epson ESC/P2, IBM ProPrinter	Maximum print speed	450 cps
		Normal print speed	400 cps
		Character pitch	10,12,15,17,17.1,20 cpi

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.