

LevelOne KVM-9036 KVM extender

Artikel	21230537
Herstellernummer	KVM-9036
EAN	4015867229576
LevelOne	



The KVM-9036 Cat.5 USB Extender Kit is a pair of devices (Transmitter and Receiver) for highdensity applications where you want full use of the keyboard, mouse, and monitor, but there is no room for a server nearby.It allows users to access a computer, server or KVM switch up to 100m away. Or for applications where you want to put all computers in a safe place, all that is needed on the desktop is a single keyboard, monitor, and mouse.KVM-9036 has auto-adjustable RGB gain/delay control capability for superior video performance.

Zusammenfassung

The KVM-9036 Cat.5 USB Extender Kit is a pair of devices (Transmitter and Receiver) for highdensity applications where you want full use of the keyboard, mouse, and monitor, but there is no room for a server nearby.It allows users to access a computer, server or KVM switch up to 100m away. Or for applications where you want to put all computers in a safe place, all that is needed on the desktop is a single keyboard, monitor, and mouse.KVM-9036 has auto-adjustable RGB gain/delay control capability for superior video performance.

LevelOne KVM over Cat.5 Extender, Transmitter & receiver, Wired, 100 m, Cat5, Cat5e, 1920 x 1200 pixels, Hotkeys, Push-buttons

LevelOne KVM over Cat.5 Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 100 m. Transmitter video port type: VGA, Transmitter local video port type: VGA, Transmitter local keyboard/mouse port type: USB. Receiver local video port type: VGA, Receiver local keyboard/mouse port type: USB. USB port type: USB Type-B. Transmitter width: 13.1 cm, Transmitter depth: 6.5 cm, Transmitter height: 2.6 cm

Merkmale

Sustainability

Sustainability compliance Yes

Other features

Firmware upgradeable Yes

Packaging data

Package width	204 mm
Package depth	176 mm
Package height	139 mm
Package weight	1.69 kg

Transmitter

Compliance certificates	CE, Federal Communications Commission (FCC), UKCA, WEEE
-------------------------	---

Transmitter video port type	VGA
Transmitter local video port	Yes
Transmitter local video port type	VGA
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1

Ports & interfaces

USB port type	USB Type-B
USB 2.0 ports quantity	2

Packaging content

AC adapter included	Yes
Cables included	KVM
Quick installation guide	Yes

Receiver

Receiver local video port type	VGA
Receiver local keyboard/mouse port type	USB
RJ-45 ports quantity (receiver)	1

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-5 - 65 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Transmitter width	13.1 cm
Transmitter depth	6.5 cm
Transmitter height	2.6 cm
Transmitter weight	586 g
Receiver width	13.1 cm
Receiver depth	6.5 cm
Receiver height	2.6 cm
Receiver weight	586 g

Logistics data

Country of origin	Taiwan
Pallet gross length	94 cm
Pallet gross width	135 cm
Pallet gross height	11.5 cm
Master (outer) case width	440 mm
Master (outer) case length	370 mm
Master (outer) case height	430 mm
Master (outer) case gross weight	21.3 kg
Products per master (outer) case	12 pc(s)

Features

Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	100 m
Cable types supported	Cat5, Cat5e
Maximum analog resolution	1920 x 1200 pixels
KVM port selection	Hotkeys, Push-buttons
On Screen Display (OSD)	Yes
Product colour	Black
Material	Metal
Plug and Play	Yes
LED indicators	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.