

Thermaltake MAGFloe 360 Ultra ARGB

Artikel	21282217
Herstellernummer	CL-W432-PL12SW-A
EAN	4711475647800
Thermaltake	



Striking Visuals, Peak Performance

Experience superior cooling with the MAGFloe Ultra ARGB Sync, blending sleek design and advanced functionality. Its 3.95" square LCD display offers stunning personalization, while SWAFAN EX fans feature quick magnetic connections and swappable blades for easy installation, tidy cable management, and ideal airflow direction.

Steady Connection with MagForce 2.0

The SWAFAN EX fans included in MAGFloe Ultra ARGB Sync are upgraded to the MagForce 2.0 connector, whose Pogo pin contact pads are TWO times larger for greater tolerance. This enhancement significantly reduces the potential faulty alignment, whether you are daisy-chaining fans together or connecting fans with cable, further boosting the installation efficiency and streamlining the building experience.

Say Goodbye to Excessive Cables

Connect your fans with SWAFAN EX's MagForce 2.0 Quick Connect Design and be free from messy cables!

Unlocks the Full Potential of RGB Lighting

With the Swappable Fan Blade Design, the MAGFloe Ultra ARGB Sync Liquid Cooler incorporates three standard blades and reverse blades, effortlessly switching between the airflow direction for intake or exhaust while fully showing lighting effects. No more sacrificing aesthetics for your airflow direction!

The Ultimate Cooling Performance of an RGB Fan

To achieve optimal cooling efficiency for high-performance systems, the SWAFAN EX12 has a maximum operating speed of 2000 RPM.

Standard Fan Blades can provide an static pressure of 2.39 mm-H₂O (Max) and 57.11 CFM (Max) airflow while maintaining under 30.6 dB-A noise level and can bring air from the front to the back.

Reverse Fan Blades can provide an static pressure of 2.02 mm-H₂O (Max) and 56.26 CFM (Max) airflow while maintaining under 32.5 dB-A noise level and can bring air from the back to the front.

Enhanced Cooling Surface With A Compact Design

The MAGFloe Ultra ARGB Sync series has a 27mm slim radiator with a thickened 20mm copper chamber, ensuring the same easy installation but with even better cooling performance.

Keep it COLD with Copper

The high-performance copper base plate accelerates heat conductivity. The high-quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore, no refill is required.

Cleaning Fans are now Easy and Fun!

Pop and insert, it is that easy.

If you want, you can even rinse the fan blades with water, just make sure you dry them thoroughly and apply the bearing lubricant that is included in the package if needed.

Personalize Your LCD Display

The MAGFloe Ultra ARGB Sync features a premium 3.95" Square LCD Display. This impressive-sized LCD screen comes with 480 x 480 resolution, delivering vibrant, clear, and high-quality visuals that enhance the aesthetics of your build.

Fully Customizable with TT RGB Plus 2.0

Monitor frequency and real-time temperature directly from the 3.95" Square LCD Display, or customize start-up and standby screens by uploading images or GIFs to add extra flair with the TT RGB Plus 2.0 software.

Quick Upload Visuals with TT PlayLink App

With the TT PlayLink app, customizing your LCD displays is much easier through a smartphone.

Whether uploading pictures and videos from your gallery or capturing live moments with the camera or streaming functions, personalizing your screen is more convenient than ever!

TT RGB PLUS Ecosystem

Light up your system with almost limitless possibilities and synchronize your TT RGB PLUS compatible products to create a RGB ecosystem that is truly unique to you.

TT RGB PLUS Software

The new version of Thermaltake's TT RGB PLUS patented software, providing more lighting effects and PC monitoring functions.

TT PlayLink Mobile App

TT PlayLink is a new mobile application that simplifies the customization of PC LCD screens, enabling quick visual uploads and live streaming from a smartphone.

Sync with Motherboard RGB Software

Designed to synchronize with ASUS Aura Sync, GIGABYTE RGB Fusion, MSI Mystic Light Sync, and ASRock Polychrome. It supports motherboards with a 5V addressable RGB header, allowing you to control the lights directly from the software mentioned above without installing any extra lighting software or controllers. For more details, please visit ASUS, GIGABYTE, MSI, and ASRock official websites.

Zusammenfassung

Striking Visuals, Peak Performance

Experience superior cooling with the MAGFloe Ultra ARGB Sync, blending sleek design and advanced functionality. Its 3.95" square LCD display offers stunning personalization, while SWAFAN EX fans feature quick magnetic connections and swappable blades for easy installation, tidy cable management, and ideal airflow direction.

Steady Connection with MagForce 2.0

The SWAFAN EX fans included in MAGFloe Ultra ARGB Sync are upgraded to the MagForce 2.0 connector, whose Pogo pin contact pads are TWO times larger for greater tolerance. This enhancement significantly reduces the potential faulty alignment, whether you are daisy-chaining fans together or connecting fans with cable, further boosting the installation efficiency and streamlining the building experience.

Say Goodbye to Excessive Cables

Connect your fans with SWAFAN EX's MagForce 2.0 Quick Connect Design and be free from messy cables!

Unlocks the Full Potential of RGB Lighting

With the Swappable Fan Blade Design, the MAGFloe Ultra ARGB Sync Liquid Cooler incorporates three standard blades and reverse blades, effortlessly switching between the airflow direction for intake or exhaust while fully showing lighting effects. No more sacrificing aesthetics for your airflow direction!

The Ultimate Cooling Performance of an RGB Fan

To achieve optimal cooling efficiency for high-performance systems, the SWAFAN EX12 has a maximum operating speed of 2000 RPM.

Standard Fan Blades can provide an static pressure of 2.39 mm-H2O (Max) and 57.11 CFM (Max) airflow while maintaining under 30.6 dB-A noise level and can bring air from the front to the back.

Reverse Fan Blades can provide an static pressure of 2.02 mm-H₂O (Max) and 56.26 CFM (Max) airflow while maintaining under 32.5 dB-A noise level and can bring air from the back to the front.

Enhanced Cooling Surface With A Compact Design

The MAGFloe Ultra ARGB Sync series has a 27mm slim radiator with a thickened 20mm copper chamber, ensuring the same easy installation but with even better cooling performance.

Keep it COLD with Copper

The high-performance copper base plate accelerates heat conductivity. The high-quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore, no refill is required.

Cleaning Fans are now Easy and Fun!

Pop and insert, it is that easy.

If you want, you can even rinse the fan blades with water, just make sure you dry them thoroughly and apply the bearing lubricant that is included in the package if needed.

Personalize Your LCD Display

The MAGFloe Ultra ARGB Sync features a premium 3.95" Square LCD Display. This impressive-sized LCD screen comes with 480 x 480 resolution, delivering vibrant, clear, and high-quality visuals that enhance the aesthetics of your build.

Fully Customizable with TT RGB Plus 2.0

Monitor frequency and real-time temperature directly from the 3.95" Square LCD Display, or customize start-up and standby screens by uploading images or GIFs to add extra flair with the TT RGB Plus 2.0 software.

Quick Upload Visuals with TT PlayLink App

With the TT PlayLink app, customizing your LCD displays is much easier through a smartphone.

Whether uploading pictures and videos from your gallery or capturing live moments with the camera or streaming functions, personalizing your screen is more convenient than ever!

TT RGB PLUS Ecosystem

Light up your system with almost limitless possibilities and synchronize your TT RGB PLUS compatible products to create a RGB ecosystem that is truly unique to you.

TT RGB PLUS Software

The new version of Thermaltake's TT RGB PLUS patented software, providing more lighting effects and PC monitoring functions.

TT PlayLink Mobile App

TT PlayLink is a new mobile application that simplifies the customization of PC LCD screens, enabling quick visual uploads and live streaming from a smartphone.

Sync with Motherboard RGB Software

Designed to synchronize with ASUS Aura Sync, GIGABYTE RGB Fusion, MSI Mystic Light Sync, and ASRock Polychrome. It supports motherboards with a 5V addressable RGB header, allowing you to control the lights directly from the software mentioned above without installing any extra lighting software or controllers. For more details, please visit ASUS, GIGABYTE, MSI, and ASRock official websites.

Thermaltake MAGFloe 360 Ultra ARGB, All-in-one liquid cooler, 12 cm, 500 RPM, 2000 RPM, Black

Thermaltake MAGFloe 360 Ultra ARGB. Type: All-in-one liquid cooler, Fan diameter: 12 cm, Rotational speed (min): 500 RPM, Rotational speed (max): 2000 RPM, Maximum air pressure: 2.39 mmH₂O. Product colour: Black

Merkmale

		Design	
Packaging content		Product colour	Black
Screws included		Radiator material	Aluminum
Yes		Number of fans	3 fan(s)
		Illumination LED	Yes
		Illumination colour	Multi
Power		Water block material	Copper
		Display type	TFT

Pump power consumption	5.16 W
Thermal Design Power (TDP)	355 W
Pump voltage	12 V
Pump current	430 mA

Weight & dimensions

Radiator width	39.6 cm
Radiator depth	12 cm
Radiator height	2.7 cm
Tube length	46 cm
Fan dimensions (W x D x H)	120 x 120 x 25 mm

Performance

Suitable location	Processor
Type	All-in-one liquid cooler
Fan diameter	12 cm
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1700, LGA 1851, LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket AM5, Socket FM1, Socket FM2
Rotational speed (min)	500 RPM
Rotational speed (max)	2000 RPM
Noise level (high speed)	30.6 dB
Maximum airflow	57.11 cfm
Maximum air pressure	2.39 mmH2O
Pulse-width modulation (PWM) support	Yes
Quantity per pack	1 pc(s)
Pump motor speed (min)	1500 RPM
Pump motor speed (max)	3300 RPM

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.