

# Digitus DN-49101 rack cabinet

---



<b>Artikel</b>	21288875
<b>Herstellernummer</b>	DN-49101
<b>EAN</b>	4016032493631
Digitus	

The DIGITUS® wall-mounted enclosure SOHO PRO series is characterized by its efficient delivery in an optimized flat pack and particularly user-friendly installation.

- Compact housing for installations where space is limited
- Simplified logistics: delivered unassembled in an optimized flat pack
- Quickly ready for use: Particularly user-friendly, quick installation with just a few screws
- Flexible cable routing options thanks to protected openings in the roof and floor
- Lockable safety glass door with 200° door opening angle
- Depth-adjustable 254 mm (10") profile rails
- Load capacity for the installation of components: 30 kg

Whether in the home, office or in sub-distribution boards with limited space: With the compact 254 mm (10") solutions from the SOHO PRO series, you can install your network wherever you want. Available in three height units (6U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the roof and base. A pair of galvanized 254 mm (10") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

## Zusammenfassung

---

The DIGITUS® wall-mounted enclosure SOHO PRO series is characterized by its efficient delivery in an optimized flat pack and particularly user-friendly installation.

- Compact housing for installations where space is limited
- Simplified logistics: delivered unassembled in an optimized flat pack
- Quickly ready for use: Particularly user-friendly, quick installation with just a few screws
- Flexible cable routing options thanks to protected openings in the roof and floor
- Lockable safety glass door with 200° door opening angle
- Depth-adjustable 254 mm (10") profile rails
- Load capacity for the installation of components: 30 kg

Whether in the home, office or in sub-distribution boards with limited space: With the compact 254 mm (10") solutions from the SOHO PRO series, you can install your network wherever you want. Available in three height units (6U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the roof and base. A pair of galvanized 254 mm (10") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035)

and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

Digitus SOHO PRO wall-mounted enclosure - 254 mm (10") - 315x300 mm (WxD), Wall mounted rack, 6U, 60 kg, Key lock, Rack rails, Cable management

Digitus SOHO PRO wall-mounted enclosure - 254 mm (10") - 315x300 mm (WxD). Type: Wall mounted rack, Rack capacity: 6U, Maximum weight capacity: 60 kg, Key lock, Cable management, Rack rails, International Protection (IP) code: IP20. Weight: 4.58 kg. Product colour: Black

## Merkmale

### Packaging data

Quick installation guide	Yes
Package width	349 mm
Package depth	330 mm
Package height	153 mm
Package weight	4.98 kg

### Weight & dimensions

Size (imperial)	25.4 cm (10")
Width	316 mm
Depth	298 mm
Height	324 mm
Weight	4.58 kg

### Features

Rack capacity	6U
Type	Wall mounted rack
Maximum weight capacity	60 kg
Product colour	Black
Material	Steel
Frame type	Closed
Back door construction	Steel
Front door construction	Glass
Side panel construction	Steel
Side panel style	Blind
Back door style	Blind
Front door style	Glass door
Key lock	Yes
Front door key lock	Yes
Rack rails	Yes
Adjustable mounting rails	Yes
Adjustable depth	Yes
Cooling type	Passive
Cable management	Yes
Door opening angle	200°
International Protection (IP) code	IP20

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.