

# Lexar LNM790X008T-RNNNG internal solid state drive

---

**Artikel  
Herstellernummer**  
Lexar

21295654  
LNM790X008T-RNNNG



## Incredible speeds to get the job done

With a blazing 7400MB/s sequential read, 6500MB/s sequential write<sup>1</sup> and random read speeds of up to 1,000,000 IOPs, the Lexar® NM790 SSD has the performance to put you across the finish line first or easily meet your most demanding deadlines.

## Twice as fast

At 2x as fast as PCIe Gen3 SSDs<sup>2</sup>, the Lexar® NM790 M.2 2280 PCIe Gen 4x4 NVMe SSD helps you perform at your best, fast.

## Zusammenfassung

---

### Incredible speeds to get the job done

With a blazing 7400MB/s sequential read, 6500MB/s sequential write<sup>1</sup> and random read speeds of up to 1,000,000 IOPs, the Lexar® NM790 SSD has the performance to put you across the finish line first or easily meet your most demanding deadlines.

### Twice as fast

At 2x as fast as PCIe Gen3 SSDs<sup>2</sup>, the Lexar® NM790 M.2 2280 PCIe Gen 4x4 NVMe SSD helps you perform at your best, fast.

Lexar LNM790X008T-RNNNG, 8 TB, M.2

Lexar LNM790X008T-RNNNG. SSD capacity: 8 TB, SSD form factor: M.2, Component for: PC/Game console

## Merkmale

---

### Brand-specific features

Brand specific technologies SLC Caching

### Operational conditions

Operating temperature (T-T) 0 - 70 °C  
Storage temperature (T-T) -40 - 85 °C  
Vibration resistance 20 G

### Weight & dimensions

Width	22 mm
Depth	80 mm
Height	2.45 mm
Weight	6 g

### Features

NVMe version	2.0
SSD capacity	8 TB

## Other features

Sequential reading	7400 MB/s
Sequential writing speed	6500 MB/s
Warranty period	5 year(s)

SSD form factor	M.2
Interface	PCI Express 4.0
NVMe	Yes
Component for	PC/Game console
M.2 SSD size	2280 (22 x 80 mm)
PCI Express interface data lanes	x4
Mean time between failures (MTBF)	1500000 h

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.