

FSP/Fortron FP 2000



Artikel
Herstellernummer
EAN
FSP/Fortron

213063
PPF12A0800
4711140487663

The line-interactive FP-Series UPS with a compact size can provide stable power protection against surges and spikes. It is ideal for PC users or small business companies, as well as for small telecom applications.

Its embedded microprocessor controller guarantees high reliability. It can automatically restart while AC power is recovering. With Simulated sine wave, off-mode charging, and cold start function, it will be a good choice.

- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Compact Size
- Simulated sine wave
- Off-mode charging
- Cold start function
- Generator compatible

Zusammenfassung

The line-interactive FP-Series UPS with a compact size can provide stable power protection against surges and spikes. It is ideal for PC users or small business companies, as well as for small telecom applications.

Its embedded microprocessor controller guarantees high reliability. It can automatically restart while AC power is recovering. With Simulated sine wave, off-mode charging, and cold start function, it will be a good choice.

- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Compact Size
- Simulated sine wave
- Off-mode charging
- Cold start function
- Generator compatible

FSP/Fortron FP 2000, Line-Interactive, 2 kVA, 1200 W, Sine, 162 V, 290 V

FSP/Fortron FP 2000. UPS topology: Line-Interactive, Output power capacity: 2 kVA, Output power: 1200 W. AC outlet types: Type E / F, AC outlets quantity: 4 AC outlet(s). Battery recharge time: 6 h. Form factor: Mini Tower, Product colour: Black. Width: 130 mm, Depth: 320 mm, Height: 182 mm

Merkmale

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Other features

Battery type	9 AH
--------------	------

Battery

Number of batteries supported	2
Battery recharge time	6 h

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-0 - 90% H)	

Design

Form factor	Mini Tower
Product colour	Black
LED indicators	Y

Ports & interfaces

AC outlet types	Type E / F
AC outlets quantity	4 AC outlet(s)
Number of type F outputs	4

Weight & dimensions

Width	130 mm
Depth	320 mm
Height	182 mm
Weight	11 kg
Package width	190 mm
Package depth	390 mm
Package height	275 mm

Features

UPS topology	Line-Interactive
Output power capacity	2 kVA
Output power	1200 W
Waveform	Sine
Input operation voltage (min)	162 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output frequency regulation	60 / 50 Hz
Output voltage regulation	10%
Response time	6 ms
Noise level	40 dB
Power protection features	Overcharge, Overload
Audible alarm(s)	Y
Audible alarm modes	Battery replacement

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.