FSP iFP 600 uninterruptible power supply (UPS)



Artikel Herstellernummer EAN FSP 213064 PPF3602700 4713224522307

The iFP series is equipped with automatic voltage regulation to reduce the impact of unstable voltage on equipment. The intelligent UPS' functions can also provide power during outages, and the battery automatically charges when power is restored. FSP's intelligent UPS can provide equipment with an uninterrupted supply of power at any time.

Zusammenfassung

The iFP series is equipped with automatic voltage regulation to reduce the impact of unstable voltage on equipment. The intelligent UPS' functions can also provide power during outages, and the battery automatically charges when power is restored. FSP's intelligent UPS can provide equipment with an uninterrupted supply of power at any time.

FSP iFP 600, Line-Interactive, 0.6 kVA, 360 W, Sine, 140 V, 290 V

FSP iFP 600. UPS topology: Line-Interactive, Output power capacity: 0.6 kVA, Output power: 360 W. AC outlet types: Type F, AC outlets quantity: 2 AC outlet(s), USB port type: USB Type-B. Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Mini Tower, Product colour: Black, Control type: Buttons. Compliance certificates: CE, cTUVus

Merkmale

		Battery	
Certificates		Battery capacity	7 Ah
		Battery voltage	12 V
Compliance certificates	CE, cTUVus	Number of batteries supported	1
Logistics data		Design	
Harmonized System (HS)	85078000	Form factor	Mini Tower
code		Product colour	Black
		Control type	Buttons
		Display type	LCD
Other features			

Packaging content UPS & user manual

Weight & dimensions

Sustainability

Sustainability compliance Yes

Operational conditions

Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-0 - 90% H)

Packaging content

Batteries included	Yes
Manual	Yes

Width	101 mm	
Depth	300 mm	
Height	142 mm	
Weight	4.25 kg	

Ports & interfaces

AC outlet types	Type F
AC outlets quantity	2 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2

Features

UPS topology	Line-Interactive
Output power capacity	0.6 kVA
Output power	360 W
Waveform	Sine
Input operation voltage (min)	140 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	110 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	10%
Automatic Voltage Regulation	Yes
(AVR)	
Response time	6 ms
Noise level	40 dB
Power protection features	Battery discharge, Overcharge, Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Auto-restart	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.