Artikel Herstellernummer EAN FSP/Fortron 213077 PPF9001401 4713224520600



FSP Champ is the high density version of double-conversion online UPS with an output power factor that reaches 0.9 and featured with ECO mode for energy saving.

FSP Champ Rack is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Zusammenfassung

FSP Champ is the high density version of double-conversion online UPS with an output power factor that reaches 0.9 and featured with ECO mode for energy saving.

FSP Champ Rack is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

FSP/Fortron Champ Rack 1K, Double-conversion (Online), 1 kVA, 900 W, Pure sine, 100 V, 240 V

FSP/Fortron Champ Rack 1K. UPS topology: Double-conversion (Online), Output power capacity: 1 kVA, Output power: 900 W. Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 438 mm, Depth: 310 mm, Height: 88 mm

Merkmale

Logistics data

Harmonized System (HS) 85078000 code

Ports & interfaces

USB port	Y	
USB 2.0 ports quantity	1	
RS-232 ports	1	

Operational conditions

Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-20 - 90% H)

Battery

Battery capacity9 AhBattery voltage12 VNumber of batteries2supported12 V

Design

Form factor	Rackmount
Rack capacity	2U
Product colour	Black

Weight & dimensions

Width	438 mm
Depth	310 mm
Height	88 mm
Weight	12 kg

Features

UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	900 W
Waveform	Pure sine
Input operation voltage (min)	100 V
Input operation voltage (max)	240 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	100 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	±0.5 Hz
Output voltage regulation	±1%
Power factor	0.9
Noise level	50 dB

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.