

FSP/Fortron Champ Rack 3K

Artikel	213079
Herstellernummer	PPF27A1102
EAN	4713224520624
FSP/Fortron	



FSP Champ is the high density version of double-conversion online UPS with an output power factor that reaches 0.9 and featured with ECO mode for energy saving.

FSP Champ Rack is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Zusammenfassung

FSP Champ is the high density version of double-conversion online UPS with an output power factor that reaches 0.9 and featured with ECO mode for energy saving.

FSP Champ Rack is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

FSP/Fortron Champ Rack 3K, Double-conversion (Online), 3 kVA, 2700 W, Pure sine, 100 V, 240 V

FSP/Fortron Champ Rack 3K. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2700 W. Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 438 mm, Depth: 630 mm, Height: 88 mm

Merkmale

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Ports & interfaces

USB port	Y
USB 2.0 ports quantity	1
RS-232 ports	1

Weight & dimensions

Width	438 mm
Depth	630 mm
Height	88 mm
Weight	29.3 kg

Features

UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Pure sine
Input operation voltage (min)	100 V
Input operation voltage (max)	240 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	100 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	±0.5 Hz
Output voltage regulation	±1%
Power factor	0.9
Noise level	50 dB

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-20 - 90% H)	

Battery

Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	6

Design

Form factor	Rackmount
Rack capacity	2U
Product colour	Black

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.