

FSP/Fortron Clippers RT 3k

Artikel	213083
Herstellernummer	PPF20A0400
EAN	4713224524899
FSP/Fortron	



FSP Clippers Series Clippers series is a premium featured online double conversion UPS with Rack/Tower design and high efficiency to reduce customer's total cost of ownership. The internal hot-swappable battery increases system reliability and reduce MTTR; the parallel function is designed for future equipment expansion. Its special firmware design can adapt various applications like laser printer, ultrasound device and supporting long back-up time with battery monitoring.

Zusammenfassung

FSP Clippers Series Clippers series is a premium featured online double conversion UPS with Rack/Tower design and high efficiency to reduce customer's total cost of ownership. The internal hot-swappable battery increases system reliability and reduce MTTR; the parallel function is designed for future equipment expansion. Its special firmware design can adapt various applications like laser printer, ultrasound device and supporting long back-up time with battery monitoring.

FSP/Fortron Clippers RT 3k, Double-conversion (Online), 3000 kVA, 3000 W, Sine, 110 V, 300 V

FSP/Fortron Clippers RT 3k. UPS topology: Double-conversion (Online), Output power capacity: 3000 kVA, Output power: 3000 W. AC outlet types: C13 coupler, USB port type: USB Type-B, Serial interface type: RS-232. Battery capacity: 9 Ah, Battery voltage: 12 V, Typical backup time at full load: 33 min. Form factor: Rackmount, Product colour: Black, Display type: LCD. Width: 438 mm, Depth: 630 mm, Height: 88 mm

Merkmale

Logistics data

Harmonized System (HS) code 85078000

Weight & dimensions

Width	438 mm
Depth	630 mm
Height	88 mm
Weight	27.5 kg

Operational conditions

Operating temperature (T-T) 0 - 40 °C
Operating relative humidity (H-20 - 90% H)

Battery

Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	6

Technical details

Sustainability compliance	Y
Sustainability certificates	CE

Design

Form factor	Rackmount
Product colour	Black
Display type	LCD
Certification	EMC EN62040-2 C2

Typical backup time at full load	33 min
Battery recharge time	3 h
Hot-swap battery	Y

Ports & interfaces

AC outlet types	C13 coupler
USB port	Y
USB port type	USB Type-B
Serial interface	Y
Serial interface type	RS-232
Emergency Power Off (EPO) connector	Y

Features

UPS topology	Double-conversion (Online)
Output power capacity	3000 kVA
Output power	3000 W
Waveform	Sine
Input operation voltage (min)	110 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output frequency	46/64 Hz
Output frequency regulation	0.1 Hz
Output voltage regulation	1%
Response time	4 ms
Number of input phases	1
Power factor	0.99
Crest factor	3:1
ECO mode	Y
Total Harmonic Distortion (THD) (linear load)	2%
Total Harmonic Distortion (THD) (non-linear load)	4%
Noise level	50 dB
Surge protection	Y
Audible alarm(s)	Y
Audible alarm modes	Alarm when on battery, Fault, Overload alarm, Low battery alarm

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.