Grandstream Networks GXP-2140 IP phone

A versatile High-End IP phone, the GXP2140 supports 4 lines, includes Gigabit ports and is compatible with Grandstream's GXP2200 LCD extension module (GXP2200 EXT) making it ideal for receptionists and users who handle high call volumes. The GXP2140 includes HD audio, a 4.3 inch color screen, 5-way voice conferencing, and built-in Bluetooth support allows for use of Bluetooth headsets and transferring of phonebook and calls from paired mobile devices, the GXP2140 is perfect for Enterprise & SMB customers with the need for quality and versatility in their desktop communications.

Zusammenfassung

A versatile High-End IP phone, the GXP2140 supports 4 lines, includes Gigabit ports and is compatible with Grandstream's GXP2200 LCD extension module (GXP2200 EXT) making it ideal for receptionists and users who handle high call volumes. The GXP2140 includes HD audio, a 4.3 inch color screen, 5-way voice conferencing, and built-in Bluetooth support allows for use of Bluetooth headsets and transferring of phonebook and calls from paired mobile devices, the GXP2140 is perfect for Enterprise & SMB customers with the need for quality and versatility in their desktop communications.

Grandstream Networks GXP-2140, IP Phone, Black, Wired handset, 4 lines, 2000 entries, TFT

Grandstream Networks GXP-2140. Product type: IP Phone, Product colour: Black, Handset type: Wired handset. Lines quantity: 4 lines, Phonebook capacity: 2000 entries. Display: TFT, Display resolution: 480 x 272 pixels. Voice codecs: G.711a, G.722, G.726, G.729A, G.729B, iLBC. Ethernet LAN interface type: Gigabit Ethernet, Bluetooth version: 2.1+EDR, Supported network protocols: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP,...

Merkmale

Camera

Front camera	N

Certificates

Certification	FCC Part 15 (CFR 47) Class B; EN55022 Class B, EN55024, EN61000-3-2,

Design

Product type	IP Phone
Handset type	Wired handset
Product colour	Black

Display

Display	TFT
Display resolution	480 x 272 pixels

	EN61000-3- 3, EN 60950-1, EN62479 AS/NZS CISPR 22 Class B, AS/NZS CISPR 24, RoHS; UL 60950 (power adapter)

Logistics data

Harmonized System (HS) code	85171800

Packaging content

Number of handles included	1 pc(s)

Audio

Speakerphone	Y
Voice codecs	G.711a, G.722, G.726, G.729A, G.729B, iLBC

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-10 - 90% H)	

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
RJ-9 ports quantity	1

Touchscreen	N

Power

Power over Ethernet (PoE)	Y
AC adapter input voltage	100 - 240 V
AC adapter output voltage	12 V

Weight & dimensions

Width	228 mm
Depth	206 mm
Height	46.5 mm
Weight	980 g
Package weight	1.55 kg

Network

Ethernet LAN	Y
Ethernet LAN interface type	Gigabit Ethernet
Wi-Fi	N
Bluetooth	Y
Bluetooth version	2.1+EDR
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE,TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPv6
Quality of Service (QoS) support	Y
Security algorithms	SRTP

Phone features

Lines quantity	4 lines
Call waiting	Y
Call hold	Y
Call forwarding	Y
Conference call	Y
Phonebook capacity	2000 entries
Call park	Y
Call pick up	Y
Phonebook sharing	Y
Call transfer	Y