

# Grandstream Networks GXP-2130 IP phone



Artikel	215234
Herstellernummer	GXP-2130
EAN	6947273701569
Grandstream Networks	

The GXP2130 v2 is a standard High-End IP phone that features up to 3 lines, Gigabit ports and 8 BLF/speed-dial keys to easily monitor presence and status of other extensions and transfer calls. A 2.8 inch color LCD screen and HD audio allow for a crisp display and high quality calls. The GXP2130 v2 comes equipped with Bluetooth, Electronic Hook Switch (EHS) support for Plantronics headsets to allow for flexibility. Ideal for SMBs, enterprises and SOHOs, the GXP2130 v2 is the perfect choice for users looking for a high quality, feature rich IP phone with advanced functionality that is simple to use.

## Zusammenfassung

The GXP2130 v2 is a standard High-End IP phone that features up to 3 lines, Gigabit ports and 8 BLF/speed-dial keys to easily monitor presence and status of other extensions and transfer calls. A 2.8 inch color LCD screen and HD audio allow for a crisp display and high quality calls. The GXP2130 v2 comes equipped with Bluetooth, Electronic Hook Switch (EHS) support for Plantronics headsets to allow for flexibility. Ideal for SMBs, enterprises and SOHOs, the GXP2130 v2 is the perfect choice for users looking for a high quality, feature rich IP phone with advanced functionality that is simple to use.

Grandstream Networks GXP-2130, IP Phone, Black, Wired handset, 3 lines, 2000 entries, TFT

Grandstream Networks GXP-2130. Product type: IP Phone, Product colour: Black, Handset type: Wired handset. Lines quantity: 3 lines, Phonebook capacity: 2000 entries. Display: TFT, Display resolution: 320 x 240 pixels. Voice codecs: G.711a, G.722, G.726, G.729A, G.729B. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Bluetooth version: 2.1+EDR

## Merkmale

Camera		Design	
Front camera	N	Product type	IP Phone
		Handset type	Wired handset
		Product colour	Black
Certificates		Display	
Certification	FCC Part 15 ClassB, EN55022 ClassB, EN61000-3-2, EN61000-3-3,	Display	TFT
		Display resolution	320 x 240 pixels
		Touchscreen	N

EN55024, EN60950-1,  
EN62479 RCM: AS/ACIF  
S004; AS/NZS CISPR22/24;  
AS/NZS 60950

## Logistics data

Harmonized System (HS) code 85171800

## Packaging content

Number of handles included 1 pc(s)

## Operational conditions

Operating temperature (T-T) 0 - 40 °C  
Operating relative humidity (H-10 - 90%  
H)

## Audio

Speakerphone Y  
Microphone mute Y  
Voice codecs G.711a, G.722, G.726,  
G.729A, G.729B

## Power

Power over Ethernet (PoE) Y  
AC adapter input voltage 100 - 240 V  
AC adapter output voltage 12 V  
Power consumption (typical) 6 W  
Power consumption (PowerSave) 0.5 W

## Weight & dimensions

Width 193 mm  
Depth 211 mm  
Height 85 mm  
Weight 810 g  
Package weight 1.44 kg

## Phone features

Lines quantity 3 lines  
Call waiting Y  
Call hold Y  
Call forwarding Y  
Conference call Y  
Redialing Y  
Phonebook capacity 2000 entries

## Network

Ethernet LAN Y  
Ethernet LAN interface type Gigabit Ethernet  
Ethernet LAN data rates 10,100,1000 Mbit/s  
Wi-Fi N  
Bluetooth Y  
Bluetooth version 2.1+EDR  
Supported network protocols SIP RFC3261, TCP/IP/UDP,  
RTP/RTCP, HTTP/HTTPS, ARP,  
ICMP, DNS (A record, SRV,  
NAPTR), DHCP, PPPoE,  
TELNET, TFTP, NTP, STUN,  
SIMPLE, LLDP, LDAP, TR-069,  
802.1x, TLS, SRTP, IPv6  
Quality of Service (QoS) support Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.