

Grandstream Networks DP760 DECT repeater

Artikel	215253
Herstellernummer	DP760
EAN	6947273702238
Grandstream Networks	



The DP760 is a powerful wideband HD DECT repeater that auto associates with Grandstream’s DP750 DECT Base Station to offer extended mobility to business and residential users

The DP760 is a powerful wideband DECT repeater (wireless relay station) that auto associates to Grandstream’s DP750 DECT base station offering extended mobility to business and residential users. The DP760 extends an additional range of 300 meters outdoors and 50 meters indoors to give users the freedom to move around their home or work space. This Wideband DECT Repeater relays up to 2 concurrent HD calls. The Ethernet connection provides PoE for convenient installation and a variety of remote features including provisioning, status monitoring and repeater firmware upgrades. When paired with Grandstream’s DP750 DECT VoIP base station and DP720 handsets, the DP760 offers a powerful extended DECT solution for users looking to add coverage to their VoIP DECT system.

Zusammenfassung

The DP760 is a powerful wideband HD DECT repeater that auto associates with Grandstream’s DP750 DECT Base Station to offer extended mobility to business and residential users

The DP760 is a powerful wideband DECT repeater (wireless relay station) that auto associates to Grandstream’s DP750 DECT base station offering extended mobility to business and residential users. The DP760 extends an additional range of 300 meters outdoors and 50 meters indoors to give users the freedom to move around their home or work space. This Wideband DECT Repeater relays up to 2 concurrent HD calls. The Ethernet connection provides PoE for convenient installation and a variety of remote features including provisioning, status monitoring and repeater firmware upgrades. When paired with Grandstream’s DP750 DECT VoIP base station and DP720 handsets, the DP760 offers a powerful extended DECT solution for users looking to add coverage to their VoIP DECT system.

Grandstream Networks DP760, 1880 - 1930 MHz, 1880 - 1900 MHz, 1920 - 1930 MHz, 10 channels, 10 channels, 5 channels

Grandstream Networks DP760. Radio Frequency (RF) range: 1880 - 1930 MHz, Frequency range (EU): 1880 - 1900 MHz, Frequency range (US): 1920 - 1930 MHz. AC input frequency: 50 - 60 Hz, DC output voltage: 5 V, DC output current: 1 A. Width: 130 mm, Depth: 90 mm, Height: 28.5 mm. Package weight: 360 g, Package type: Box

Merkmale

Power		
Packaging content	AC input frequency	50 - 60 Hz

Power supply included	Y
-----------------------	---

DC output voltage	5 V
DC output current	1 A
Power over Ethernet (PoE)	Y

Packaging data

Package weight	360 g
Package type	Box

Weight & dimensions

Width	130 mm
Depth	90 mm
Height	28.5 mm
Weight	143 g

Operational conditions

Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-10 - 90% H)	

Features

Radio Frequency (RF) range	1880 - 1930 MHz
Frequency range (EU)	1880 - 1900 MHz
Frequency range (US)	1920 - 1930 MHz
GAP compatible	Y
Channels quantity	10 channels
Channels quantity (EU)	10 channels
Channels quantity (USA)	5 channels
Maximum indoor range	50 m
Maximum outdoor range	300 m
Product colour	Black
Voice codecs	G.722, G.726
Supported protocols	TCP/IP/UDP, HTTP/HTTPS, ARP/RARP, ICMP, DNS, DHCP, PPPoE, SSH, TFTP, NTP, LLDP-MED, UPnP
LED indicators	Activity, Association, Network, Power, Signal strength
Power LED	Y
Firmware upgradeable	Y
Firmware upgradeable via	Network

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.