

Grandstream Networks DP722 IP phone



| | |
|-------------------------|---------------|
| Artikel | 215260 |
| Herstellernummer | DP722 |
| EAN | 6947273702740 |
| Grandstream Networks | |

Zusammenfassung

Grandstream Networks DP722, IP Phone, Black, Grey, Wireless handset, 50 m, 350 m, 10 lines

Grandstream Networks DP722. Product type: IP Phone, Product colour: Black, Grey, Handset type: Wireless handset. Maximum indoor range: 50 m, Maximum outdoor range: 350 m. Lines quantity: 10 lines. Display: TFT, Display diagonal: 4.57 cm (1.8"), Display resolution: 128 x 160 pixels. Voice codecs: G.711alaw, G.711ulaw, G.722, G.723.1, G.729A, G.729B, OPUS, iLBC

Merkmale

Camera

| | |
|--------------|----|
| Front camera | No |
|--------------|----|

Certificates

| | |
|---------------|---|
| Certification | FCC: FCC 15B; FCC 15D; SAR (FCC 47 CFR 2.1093; IEEE 1528; IEC 62209-2); FCC 68 HAC; FCC ID CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 60950-1;EN 301 489-1/-6; EN 301 406; EN 50332-2; SAR(EN50360;EN50566;EN 50663;EN62209-1; EN62209-2; EN 62479); RED NB RCM: AS/NZS CISPR32; |
|---------------|---|

Weight & dimensions

| | |
|----------------------------|--------------------|
| Handset dimensions (WxDxH) | 50 x 28.1 x 158 mm |
| Handset weight | 110 g |
| Package weight | 328 g |

Audio

| | |
|------------------------|--|
| Speakerphone | Yes |
| Voice codecs | G.711alaw, G.711ulaw, G.722, G.723.1, G.729A, G.729B, OPUS, iLBC |
| Noise reduction | Yes |
| Automatic gain control | Yes |

Battery

| | |
|--------------------|-----------------------------|
| Battery technology | Nickel-Metal Hydride (NiMH) |
| Battery type | AAA |

AS/NZS 60950.1;AS/CA
S004;AS/ACIF S040.
ANATEL, EAC, UL

Battery capacity 800 mAh
Number of batteries supported 2

Logistics data

Harmonized System (HS) code 85171800

Management features

Handset keys 23
Firmware upgradeable Yes

Design

Product type IP Phone
Handset type Wireless handset
Product colour Black, Grey

Network

Ethernet LAN No
Wi-Fi No
Bluetooth No

Performance

Maximum indoor range 50 m
Maximum outdoor range 350 m
Hearing aid compatibility Yes

Ports & interfaces

Headset connectivity 3.5 mm
USB 2.0 ports quantity 1
Headphone outputs 1

Display

Display TFT
Display diagonal 4.57 cm (1.8")
Display resolution 128 x 160 pixels
Touchscreen No

Operational conditions

Operating temperature (T-T) -10 - 50 °C
Operating relative humidity (H-H) 10 - 90%
Storage relative humidity (H-H) 10 - 90%
Storage temperature (T-T) -20 - 60 °C

Packaging content

Quick start guide Yes
Number of handles included 1 pc(s)
AC adapter included Yes
Charger Yes

Power

Power over Ethernet (PoE) No
AC adapter input voltage 100 - 240 V
Input frequency 50/60 Hz
Input current 5 A
Standby time 250 h
Talk time 20 h

Phone features

Lines quantity 10 lines
Answering machine Yes
Call waiting Yes
Call hold Yes
Call forwarding Yes
Conference call Yes
Call park Yes
Call pick up Yes
Phonebook sharing Yes
Call transfer Yes
Message-waiting indicator (MWI) Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.