

Grandstream Networks DP730 IP phone



Artikel	215261
Herstellernummer	DP730
EAN	6947273702757
Grandstream Networks	

Zusammenfassung

Grandstream Networks DP730, IP Phone, Black, Grey, Wireless handset, 50 m, 400 m, 10 lines

Grandstream Networks DP730. Product type: IP Phone, Product colour: Black, Grey, Handset type: Wireless handset. Maximum indoor range: 50 m, Maximum outdoor range: 400 m. Lines quantity: 10 lines. Display: TFT, Display diagonal: 6.1 cm (2.4"), Display resolution: 240 x 320 pixels. Voice codecs: G.711alaw, G.711ulaw, G.722, G.723.1, G.729A, G.729B, OPUS, iLBC

Merkmale

Camera

Front camera	N
--------------	---

Certificates

Certification	FCC: FCC 15B; FCC 15D; SAR (FCC 47 CFR 2.1093; IEEE 1528; IEC 62209-2); FCC 68 HAC; FCC ID CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 60950-1;EN 301 489-1/-6; EN 301 406; EN 50332-2; SAR(EN50360;EN50566;EN 50663;EN62209-1; EN62209-2; EN 62479); RED NB RCM: AS/NZS CISPR32;
---------------	--

Weight & dimensions

Handset dimensions (WxDxH)	52.5 x 21.8 x 168.5 mm
Handset weight	180 g
Package weight	465 g

Audio

Speakerphone	Y
Voice codecs	G.711alaw, G.711ulaw, G.722, G.723.1, G.729A, G.729B, OPUS, iLBC
Noise reduction	Y
Automatic gain control	Y

Design

Product type	IP Phone
Handset type	Wireless handset

AS/NZS 60950.1;AS/CA
S004;AS/ACIF S040.
ANATEL, EAC, UL

Product colour Black, Grey
Backlight keypad Y

Logistics data

Harmonized System (HS) code 85171800

Management features

Handset keys 27
Firmware upgradeable Y

Battery

Battery technology Lithium-Ion (Li-Ion)
Battery capacity 1500 mAh
Number of batteries supported 1

Network

Ethernet LAN N
Wi-Fi N
Bluetooth N

Performance

Maximum indoor range 50 m
Maximum outdoor range 400 m
Hearing aid compatibility Y

Ports & interfaces

Headset connectivity 3.5mm
USB 2.0 ports quantity 1
Headphone outputs 1

Display

Display TFT
Display diagonal 6.1 cm (2.4")
Display resolution 240 x 320 pixels
Touchscreen N

Operational conditions

Operating temperature (T-T) -10 - 50 °C
Operating relative humidity (H-H) 10 - 90%
Storage relative humidity (H-H) 10 - 90%
Storage temperature (T-T) -20 - 60 °C

Packaging content

Quick start guide Y
Number of handles included 1 pc(s)
AC adapter included Y
Charger Y

Power

Power over Ethernet (PoE) N
AC adapter input voltage 100 - 240 V
Input frequency 50/60 Hz
Standby time 500 h
Talk time 40 h

Phone features

Lines quantity 10 lines
Answering machine Y
Call waiting Y
Call hold Y
Call forwarding Y
Conference call Y
Call park Y
Call pick up Y
Phonebook sharing Y
Call transfer Y
Message-waiting indicator (MWI) Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.