

Grandstream Networks DP752 DECT base station



Artikel	215262
Herstellernummer	DP-752
EAN	6947273702733
Grandstream Networks	

Zusammenfassung

Grandstream Networks DP752, 400 m, SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A, SRV, NAPTR), DHCP, PPPoE,...., 256-bit AES, HTTPS, MD5, SRTP, SSL/TLS, AJP, AMR-WB, CNG, G.711alaw, G.711ulaw, G.722, G.722.2, G.723.1, G.726-32, G.729A, G.729B, OPUS,...., Grandstream Networks DP730, DP722, DP720, Black

Grandstream Networks DP752. Maximum range: 400 m, Supported network protocols: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A, SRV, NAPTR), DHCP, PPPoE,...., Security algorithms: 256-bit AES, HTTPS, MD5, SRTP, SSL/TLS. Product colour: Black, Certification: FCC: FCC 15B; FCC 15D; MPE; FCC ID CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 60950-1;.... Dimensions (WxDxH): 64.98 x 105 x 140.31 mm, Weight: 140 g, Package weight: 370 g

Merkmale

Logistics data

Harmonized System (HS) code	85177900
-----------------------------	----------

Power

Power over Ethernet (PoE)	Y
---------------------------	---

Design

Product colour	Black
Certification	FCC: FCC 15B; FCC 15D; MPE; FCC ID CE: EN 55032;

Operational conditions

Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Dimensions (WxDxH)	64.98 x 105 x 140.31 mm
Weight	140 g
Package weight	370 g

Call management

Conference call	Y
Number of parallel conferences	3

EN 55035; EN 61000-3-2; EN 61000-3-3; EN 60950-1; EN 301 489-1/-6; EN 301 406; EN 50385; RED NB Cert RCM: AS/NZS 32; AS/NZS 60950.1 ANATEL: ANATEL, EAC, UL

Call waiting	Y
Call forwarding	Y
Call transfer	Y
Call hold	Y
Do not disturb function	Y

Ports & interfaces

Ethernet LAN	Y
Ethernet LAN (RJ-45) ports	1

Performance

Number of handsets supported (max)	5
Maximum range	400 m
Comfort noise generation (CNG)	Y
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP
Security algorithms	256-bit AES, HTTPS, MD5, SRTP, SSL/TLS
Voice codecs	AJB, AMR-WB, CNG, G.711alaw, G.711ulaw, G.722, G.722.2, G.723.1, G.726-32, G.729A, G.729B, OPUS, PLC, VAD, iLBC
Quality of Service (QoS) support	Y
Firmware upgradeable	Y
Compatible products	Grandstream Networks DP730, DP722, DP720

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.