

Grandstream Networks GRP2612P IP phone



Artikel
Herstellernummer
EAN
Grandstream Networks

215272
GRP2612P
6947273702818

The GRP2612 features a sleek design and a suite of next-generation features including WiFi support on the GRP2612W and PoE on the GRP2612P. Key features include 16 virtual multi-purpose keys (VPKs), a color LCD with swappable face plates for easy logo customization and more. The GRP series includes carrier-grade security features to provide enterpriselevel security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2612 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints.

Zusammenfassung

The GRP2612 features a sleek design and a suite of next-generation features including WiFi support on the GRP2612W and PoE on the GRP2612P. Key features include 16 virtual multi-purpose keys (VPKs), a color LCD with swappable face plates for easy logo customization and more. The GRP series includes carrier-grade security features to provide enterpriselevel security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2612 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints.

Grandstream Networks GRP2612P, IP Phone, Black, Wired handset, In-band, Out-of band, SIP info, Supervisor, User, 2 lines

Grandstream Networks GRP2612P. Product type: IP Phone, Product colour: Black, Handset type: Wired handset. Dual-Tone Multi-Frequency (DTMF) modes: In-band, Out-of band, SIP info, Password protection type: Supervisor, User. Lines quantity: 2 lines. Volume control: Buttons. Display: TFT, Display diagonal: 6.1 cm (2.4"), Display resolution: 320 x 240 pixels

Merkmale

Camera

Front camera N

Packaging content

Quick start guide	Y
Number of handles included	1 pc(s)
Cables included	LAN (RJ-45)

Logistics data

Harmonized System (HS) 85171800

Power

Power over Ethernet (PoE) Y

code	
------	--

AC adapter input voltage	100 - 240 V
AC adapter output voltage	5 V

Audio

Speakerphone	Y
Voice codecs	G.711a, G.711u, G.722, G.723, G.726, G.729A, G.729B, OPUS, iLBC

Performance

Dual-Tone Multi-Frequency (DTMF) modes	In-band, Out-of band, SIP info
Password protection type	Supervisor, User

Ports & interfaces

Ethernet LAN (RJ-45) ports	2
RJ-9 ports quantity	1

Design

Product type	IP Phone
Handset type	Wired handset
Product colour	Black

Management features

Volume control	Buttons
Number of programmable keys	4
Firmware upgradeable	Y

Weight & dimensions

Width	203 mm
Depth	193 mm
Height	52.1 mm

Display

Display	TFT
Display diagonal	6.1 cm (2.4")
Display resolution	320 x 240 pixels
Touchscreen	N

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-10 - 60 °C

Network

Ethernet LAN	Y
Ethernet LAN interface type	Fast Ethernet
Bluetooth	N
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
Quality of Service (QoS) support	Y
Security algorithms	256-bit AES, MD5, SRTP, SSL/TLS

Phone features

Lines quantity	2 lines
Answering machine	Y
Call log entries	1000
Call waiting	Y
Call hold	Y
Call forwarding	Y
Conference call	Y
Call park	Y
Call pick up	Y
Phonebook sharing	Y
Call transfer	Y