Grandstream Networks GDS3702 audio intercom system



Artikel Herstellernummer EAN 215951 GDS3702 6947273703785

Grandstream Networks

The GDS3702 is an HD Audio IP Intercom System to offer remote facility access control for buildings of all sizes. This device includes a built-in microphone and speaker to support intercom functionality, supports integration with electric locks for locking and unlocking doors, and offers alarm-in and alarm out support for integration with existing security systems. The GDS3702 works with Grandstream's free management software, GDS Manager. It features SIP/VoIP technology with 2-way HD audio, IP66 level weatherproof casing, and is vandal resistant. The combination of the GDS3702, Grandstream's IP Phones, Wave mobile app, and other 3rd party IP devices provide a complete end-to-end solution for access control, and intercom needs.

Zusammenfassung

The GDS3702 is an HD Audio IP Intercom System to offer remote facility access control for buildings of all sizes. This device includes a built-in microphone and speaker to support intercom functionality, supports integration with electric locks for locking and unlocking doors, and offers alarm-in and alarm out support for integration with existing security systems. The GDS3702 works with Grandstream's free management software, GDS Manager. It features SIP/VoIP technology with 2-way HD audio, IP66 level weatherproof casing, and is vandal resistant. The combination of the GDS3702, Grandstream's IP Phones, Wave mobile app, and other 3rd party IP devices provide a complete end-to-end solution for access control, and intercom needs.

Grandstream Networks GDS3702, Wired, IP66, -30 - 60 °C, IEEE 802.3af, CE, FCC, IC, RCM, UKCA, White

Grandstream Networks GDS3702. Connectivity technology: Wired, International Protection (IP) code: IP66, Operating temperature (T-T): -30 - 60 °C. Product colour: White, Placement: Wall. Width: 80 mm, Depth: 36 mm, Height: 173 mm

Merkmale

		Weight & dim	Weight & dimensions	
Packaging content		Width	80 mm	
		Depth	36 mm	
Outdoor unit included Y	Υ	Height	173 mm	
		Weight	672 g	

Design

Product colour	White
Placement	Wall

Features

Connectivity technology	Wired			
Buttons quantity	1			
Speakerphone	Υ			
International Protection (IP) code IP66				
Operating temperature (T-T)	-30 - 60 °C			
Power over Ethernet (PoE)	Υ			
Networking standards	IEEE 802.3af			
Compatible products	CE, FCC, IC, RCM, UKCA			

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.