

Grandstream Networks GDS 3712 Tuersprechstelle video intercom system



Artikel	215968
Herstellernummer	GDS3712
EAN	6947273703792
Grandstream Networks	

The GDS3712 is a hemispheric IP Video Intercom System that also serves as a high-definition IP surveillance camera to offer facility access control and security monitoring for buildings of all sizes. Powered by an advanced Image Sensor Processor (ISP) and state of the art image algorithms, it delivers exceptional performance without blind spots. The GDS3712 IP video intercom system features industry-leading SIP/VoIP for 2-way audio and video streaming to smart phones and SIP phones and the GDS management software. Th is system is equipped with integrated PoE for seamless installation, motion detection for security protection, lighting control switch and more. The GDS3712 can also be managed with GSURF Pro or any ONVIF-compliant video management system. It also offers a flexible HTTP API for easy integration with 3rd party applications and other surveillance systems. The combination of the GDS3712, Grandstream's IP phones, video phones, and Wave mobile app prov ides a complete end-to-end solution for access control, video intercom, and security recording needs.

Zusammenfassung

The GDS3712 is a hemispheric IP Video Intercom System that also serves as a high-definition IP surveillance camera to offer facility access control and security monitoring for buildings of all sizes. Powered by an advanced Image Sensor Processor (ISP) and state of the art image algorithms, it delivers exceptional performance without blind spots. The GDS3712 IP video intercom system features industry-leading SIP/VoIP for 2-way audio and video streaming to smart phones and SIP phones and the GDS management software. Th is system is equipped with integrated PoE for seamless installation, motion detection for security protection, lighting control switch and more. The GDS3712 can also be managed with GSURF Pro or any ONVIF-compliant video management system. It also offers a flexible HTTP API for easy integration with 3rd party applications and other surveillance systems. The combination of the GDS3712, Grandstream's IP phones, video phones, and Wave mobile app prov ides a complete end-to-end solution for access control, video intercom, and security recording needs.

Grandstream Networks GDS 3712 Tuersprechstelle, H.264, M-JPEG, 2 MP, 1920 x 1080 pixels, 1920 x 1280 pixels, 25.4 / 2.7 mm (1 / 2.7"), 30 fps

Grandstream Networks GDS 3712 Tuersprechstelle. Video formats supported: H.264, M-JPEG. Megapixel (approx.): 2 MP, Maximum image resolution: 1920 x 1080 pixels, Maximum video resolution: 1920 x 1280 pixels. Speaker power: 2 W, Voice codecs: G.711, G.722. Product colour: Silver, International Protection (IP) code: IP66, IK code: IK10. Ethernet interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Supported network protocols: TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS local upload and mass provisioning using TR-069, ARP/RARP, ICMP,...

Merkmale

Network

Display

Video formats supported	H.264, M-JPEG
-------------------------	---------------

Power

Operating voltage (door opener)	12 V
Operating current (door opener)	1 A

Audio

Built-in speaker(s)	Yes
Number of speakers	1
Speaker power	2 W
Voice codecs	G.711, G.722

Design

Product colour	Silver
International Protection (IP) code	IP66
IK code	IK10
Placement supported	Vertical
Proper use	Outdoor

Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Power over Ethernet (PoE)	Yes
Supported network protocols	TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS local upload and mass provisioning using TR-069, ARP/RARP, ICMP, LLDP-MED, DNS, DHCP, SSH, SMTP, TFTP, NTP, STUN, TLS, SRTP
Networking standards	IEEE 802.3af

Camera

Megapixel (approx.)	2 MP
Maximum image resolution	1920 x 1080 pixels
Maximum video resolution	1920 x 1280 pixels
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Maximum frame rate	30 fps
Field of view (FOV) angle	180°
Viewing angle, horizontal	150°

Technical details

Connectivity technology	Wireless
Maximum number of cameras supported	3
Wall mountable	Yes
Built-in microphone	Yes
Motion detection function	Yes
Number of buttons	1 buttons
Backlight buttons	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.